

Package ‘flowcatchR’

April 9, 2015

Type Package

Title Tools to analyze in vivo microscopy imaging data focused on tracking flowing blood cells.

Version 1.0.3

Date 2015-02-03

Maintainer Federico Marini <marinif@uni-mainz.de>

Description flowcatchR is a set of tools to analyze in vivo microscopy imaging data, focused on tracking flowing blood cells. It guides the steps from segmentation to calculation of features, filtering out particles not of interest, providing also a set of utilities to help checking the quality of the performed operations (e.g. how good the segmentation was). The main novel contribution investigates the issue of tracking flowing cells such as in blood vessels, to categorize the particles in flowing, rolling and adherent. This classification is applied in the study of phenomena such as hemostasis and study of thrombosis development.

License BSD_3_clause + file LICENSE

VignetteBuilder knitr

Suggests BiocStyle, knitr, shiny

Depends R (>= 2.10), methods, EBImage

Imports rgl, colorRamps, abind, BiocParallel

SystemRequirements ImageMagick

URL <https://github.com/federicomarini/flowcatchR>

BugReports <https://github.com/federicomarini/flowcatchR/issues>

biocViews Software, Visualization, CellBiology, Classification, Infrastructure, GUI

Author Federico Marini [aut, cre]

R topics documented:

add.contours	3
addParticles	4
axesInfo	5
candidate.platelets	5
channel.Frames	6
computeMSD	6
crop.Frames	7
export.Frames	8
export.particles	9
extractKinematics.traj	9
flowcatchR	10
Frames	11
Frames-class	11
initialize.LinkedReader	12
inspect.Frames	12
kinematics	13
KinematicsFeatures-class	14
KinematicsFeaturesSet-class	14
length.Frames	15
link.particles	15
LinkedList-class	17
matchTrajToParticles	17
MesenteriumSubset	18
normalizeFrames	18
particles	19
ParticleSet-class	19
penaltyFunctionGenerator	20
plot.TrajectorySet	20
plot2D.TrajectorySet	21
preprocess.Frames	22
read.Frames	23
read.particles	24
repmat	25
rotate.Frames	26
select.Frames	27
select.particles	27
shinyFlow	28
show,Frames-method	29
show,KinematicsFeatures-method	29
show,KinematicsFeaturesSet-method	30
show,LinkedList-method	31
show,ParticleSet-method	32
show,TrajectorySet-method	32
snap	33
toCartesianCoords	34
toPolarCoords	35

<i>add.contours</i>	3
trajectories	35
TrajectorySet-class	36

Index **37**

add.contours *Add object contours to a Frames object*

Description

Creates a Frames object containing raw information, combined with the segmented images and the relative trajectory under analysis

Usage

```
add.contours(raw.frames, binary.frames = NULL, trajectoryset = NULL,
             trajIDs = NULL, mode = "particles", col = NULL, channel = NULL)
```

Arguments

- `raw.frames` A Frames object with raw images
- `binary.frames` A Frames object with preprocessed frames
- `trajectoryset` A TrajectorySet object
- `trajIDs` Numeric vector, the ID(s) of the trajectory.
- `mode` A character string, can assume the values `particles` or `trajectories`. Defaults to `particles`
- `col` A vector of color strings
- `channel` A character string, to select which channel to process

Details

If a TrajectorySet is provided and mode is set to `trajectories`, returns a Frames with all trajectories included in the IDs vector painted accordingly. If the mode is set to `particles`, it will just plot the particles (all) on all frames. If no TrajectorySet is provided, it will be computed with default parameters. If no `binary.frames` is provided, it will be computed also with default parameters

Value

A new Frames object with contours of the objects added

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("MesenteriumSubset")
## Not run:
paintedTrajectories <- add.contours(raw.frames = MesenteriumSubset, mode = "trajectories", channel="red")
paintedParticles <- add.contours(raw.frames = MesenteriumSubset, mode = "particles", channel="red")
inspect.Frames(paintedTrajectories)
inspect.Frames(paintedParticles)

## End(Not run)
```

addParticles	<i>Combines the information from a raw Frames object and the corresponding preprocessed one</i>
--------------	---

Description

All objects are painted with a unique colour - for sake of speed

Usage

```
addParticles(raw.frames, binary.frames, col = NULL)
```

Arguments

raw.frames	A Frames object containing the raw images
binary.frames	A Frames object with the preprocessed versions of the images (e.g. segmented)
col	A color character string, to select which color will be used for drawing the contours of the particles. If not specified, it will default according to the objects provided

Value

A Frames object, whose images are the combination of the raw images with the segmented objects drawn on them

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

axesInfo *Info on the dimensions of the FOV*

Description

Auxiliary function to return the dimensions of the field of interest

Usage

```
axesInfo(frames)
```

Arguments

frames A Frames object

Value

A list object, containing the extremes of the field of interest (x-y-z, where z is time)

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

candidate.platelets *A sample ParticleSet object*

Description

The sample ParticleSet object is constituted by the platelets identified from the MesenteriumSubset data

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

channel.Frames	<i>Channel extraction for objects</i>
----------------	---------------------------------------

Description

channel

Usage

```
channel.Frames(frames, mode)
```

Arguments

frames	A Frames object
mode	A character value specifying the target mode for conversion.

Value

A Frames object with just the information on the selected channel

Examples

```
data("MesenteriumSubset")
channel.Frames(MesenteriumSubset, "red")
```

computeMSD	<i>Calculates the Mean Squared Displacement for a trajectory</i>
------------	--

Description

Calculates the Mean Squared Displacement for a trajectory

Usage

```
computeMSD(sx, sy, until = 4)
```

Arguments

sx	x axis positions along the trajectory
sy	y axis positions along the trajectory
until	how many points should be included in the Mean Squared Displacement curve

Value

A numeric vector containing the values of the MSD

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

crop.Frames

Cut borders of a Frames object

Description

Performs cropping on the Frames object, selecting how many pixels should be cut on each side

Usage

```
crop.Frames(frames, cutLeft = 5, cutRight = 5, cutUp = 5, cutDown = 5,
  cutAll = 0, testing = FALSE, ...)
```

Arguments

frames	An input Frames object
cutLeft	Amount of pixels to be cut at the side
cutRight	Amount of pixels to be cut at the side
cutUp	Amount of pixels to be cut at the side
cutDown	Amount of pixels to be cut at the side
cutAll	Amount of pixels to be cut at all sides. Overrides the single side values
testing	Logical, whether to just test the cropping or to actually perform it. Default set to FALSE
...	Arguments to be passed to display (e.g. setting the method argument)

Details

Cropping can be performed with careful choice of all cutting sides, or cropping a single value from all sides

Value

A Frames object, with cropped frames in the image slot

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("MesenteriumSubset")
crop.Frames(MesenteriumSubset)
```

export.Frames	<i>Exports a Frames object</i>
---------------	--------------------------------

Description

Writes the images contained in the image slot of the Frames object elements. The images can be exported as single frames, or as a .gif image that is composed by the single frames.

Usage

```
export.Frames(frames, dir = tempdir(), nameStub = "testExport",
  createGif = FALSE, removeAfterCreatingGif = TRUE)
```

Arguments

frames	A Frames object
dir	The path of the folder where the image should be written
nameStub	The stub for the file name, that will be used as a prefix for the exported images
createGif	Logical, whether to create or not an animated .gif file
removeAfterCreatingGif	Logical, whether to remove the single exported .png images after creating the single .gif

Value

Image files are written in the desired location

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("MesenteriumSubset")
## Not run: export.Frames(MesenteriumSubset, nameStub="subset_export_", createGif=TRUE, removeAfterCreatingGif=FAL
```

export.particles	<i>Exports a ParticleSet object</i>
------------------	-------------------------------------

Description

Writes the particles contained in the particles data frame slot of the ParticleSet object elements. A track of the provenience of the particles is stored as a comment line above the header

Usage

```
export.particles(particleset, dir = tempdir(),
  nameStub = "testExport_particles")
```

Arguments

particleset	A ParticleSet object
dir	The path of the folder where the particle sets should be written
nameStub	The stub for the file name, that will be used as a prefix for the exported particle sets

Value

Particle sets files are written in the desired location

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("candidate.platelets")
## Not run: export.particles(candidate.platelets)
```

```
extractKinematics.traj
```

Calculate a set of kinematics parameters from a single trajectory

Description

The computed set of parameters include delta.x, delta.t and delta.v (displacements and instantaneous velocity), totalTime, totalDistance, distStartToEnd, curvilinearVelocity, straightLineVelocity and linearityForwardProgression, Mean Squared Displacement, velocity autocorrelation, and more

Frames	<i>Constructor for a Frames object</i>
--------	--

Description

Constructor for a Frames object

Usage

```
Frames(x, channel)
```

Arguments

x	A multi-dimensional Image object
channel	A character vector, can be 'red', 'green', 'blue' or 'all' (if in color mode)

Value

The created Frames object.

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("MesenteriumSubset")
inputImg <- Image(MesenteriumSubset)
Frames(inputImg, "red")
```

Frames-class	<i>Frames class</i>
--------------	---------------------

Description

S4 class for storing information on multiple images belonging to the same time-lapse experiment. It is designed as a subclass of the existing Image class from the EBImage package

Slots

channel A character vector, can be 'red', 'green', 'blue' or 'all' (if in color mode)

```
initialize.LinkedParticleSet
```

Initialize a ParticleSet object for subsequent linking/tracking

Description

Initialize a ParticleSet object for subsequent linking/tracking

Usage

```
initialize.LinkedParticleSet(particleset, linkrange = 1)
```

Arguments

particleset	A ParticleSet object
linkrange	The number of frames to look for candidate particles potentially belonging to the same track

Value

A ParticleSet object with slots dedicated for the tracking pre-filled

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

```
inspect.Frames
```

Explore the frames of a Frames

Description

The first frames of a Frames are displayed in the browser, and are interactively navigable.

Usage

```
inspect.Frames(frames, nframes = NULL, display.method = "browser",
  verbose = FALSE)
```

Arguments

frames	A Frames object
nframes	The number of frames to display (default value: NULL, all are displayed)
display.method	Method for displaying, can be either raster or browser. Defaults to browser, by opening a window in the browser
verbose	Logical, whether to provide additional output on the command line alongside with the images themselves

Value

`inspect.Frames` returns an invisible `NULL`.

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("MesenteriumSubset")
## Not run: inspect.Frames(MesenteriumSubset)
```

kinematics	<i>Calculate a set of kinematics parameter from a TrajectorySet object, or a single parameter, or from a single trajectory (all possible combinations)</i>
------------	--

Description

The computed set of parameters include `delta.x`, `delta.t` and `delta.v` (displacements and instantaneous velocity), `totalTime`, `totalDistance`, `distStartToEnd`, `curvilinearVelocity`, `straightLineVelocity` and `linearityForwardProgression`, Mean Squared Displacement, velocity autocorrelation, and more. If a single trajectory is specified, the computation is performed for that trajectory alone. If a parameter is specified, only that parameter is reported, either for one or all trajectories

Usage

```
kinematics(trajectoryset, trajectoryIDs = NULL, acquisitionFrequency = 30,
           scala = 50, feature = NULL)
```

Arguments

<code>trajectoryset</code>	A TrajectorySet object
<code>trajectoryIDs</code>	The ID of a single trajectory
<code>acquisitionFrequency</code>	The frame rate of acquisition for the images, in milliseconds
<code>scala</code>	The value of micro(?)meters to which each single pixel corresponds
<code>feature</code>	Character string, the name of the feature to be computed

Value

A KinematicsFeaturesSet object, or a KinematicsFeatures object, or an atomic value, or a list(eventually coerced to a vector)

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("candidate.platelets")
platelets.trajectories <- trajectories(candidate.platelets)
# for all trajectories, all features
alltrajs.features <- kinematics(platelets.trajectories)
# for one trajectory, all features
traj11features <- kinematics(platelets.trajectories,trajectoryIDs = 11)
# for all trajectories, one feature
alltrajs.curvVel <- kinematics(platelets.trajectories,feature = "curvilinearVelocity")
```

KinematicsFeatures-class

KinematicsFeatures class

Description

S4 class for storing information on all kinematics features identified for a single trajectory

Slots

.Data A list storing the information for the kinematics features

KinematicsFeaturesSet-class

KinematicsFeaturesSet

Description

S4 class for storing information on all kinematics features identified for all trajectories. Single KinematicsFeatures objects are the element of the main list

Slots

.Data A list storing the information for the sets of kinematics features

length.Frames	<i>Compute the length of render frames in a Frames object</i>
---------------	---

Description

Compute the length of render frames in a Frames object

Usage

```
## S3 method for class Frames
length(x)
```

Arguments

x A Frames object

Value

An integer number

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("MesenteriumSubset")
length(MesenteriumSubset)
```

link.particles	<i>Links a ParticleSet object</i>
----------------	-----------------------------------

Description

Performs linking of the particles by tracking them through the frames

Usage

```
link.particles(particleset, L, R = 2, epsilon1 = 0.1, epsilon2 = 2,
  lambda1 = 1, lambda2 = 1, penaltyFunction = penaltyFunctionGenerator(),
  verboseOutput = FALSE, prog = FALSE, include.intensity = TRUE,
  include.area = TRUE)
```

Arguments

<code>particleset</code>	A ParticleSet object
<code>L</code>	Maximum number of pixels an object can move in two consecutive frames
<code>R</code>	Linkrange, i.e. the number of consecutive frames to search for potential candidate links
<code>epsilon1</code>	A numeric value, to be used in the formula. Jitter for allowing angular displacements
<code>epsilon2</code>	A numeric value, to be used in the formula. Jitter for allowing spatial displacements
<code>lambda1</code>	A numeric value. Multiplicative factor for the penalty function
<code>lambda2</code>	A numeric value. Multiplicative factor applied to the angular displacement
<code>penaltyFunction</code>	A function structured in such a way to be applied as penalty function in the linking
<code>verboseOutput</code>	Logical, whether the output should report additional intermediate steps. For debugging use mainly
<code>prog</code>	Logical, whether the a progress bar should be shown during the tracking phase
<code>include.intensity</code>	Logical, whether to include also intensity change of the particles in the cost function calculation
<code>include.area</code>	Logical, whether to include also area change of the particles in the cost function calculation

Value

A LinkedParticleSet object

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

References

I F Sbalzarini and P Koumoutsakos. "Feature point tracking and trajectory analysis for video imaging in cell biology." In: Journal of structural biology 151.2 (Aug. 2005), pp. 182-95. ISSN: 1047-8477. DOI: 10.1016/j.jsb.2005.06.002. URL: <http://www.ncbi.nlm.nih.gov/pubmed/16043363>

Examples

```
data("candidate.platelets")
tracked.platelets <- link.particles(candidate.platelets, L= 40)
```

LinkedParticleSet-class

LinkedParticleSet class

Description

S4 class for storing information of particles after they have been tracked. It inherits the slots from the ParticleSet class.

Slots

tracking A list storing all necessary information for the tracking algorithm to work, and for providing the information to the function to determine the trajectories

matchTrajToParticles *Match trajectories to related particles.*

Description

Match trajectories to the related particles in the TrajectorySet and ParticleSet objects. This function returns a new ParticleSet object that contains as additional column the trajectory ID that the particular particle was assigned to. Used also by other routines, such as [snap](#)

Usage

```
matchTrajToParticles(particleset, trajectoryset)
```

Arguments

particleset A ParticleSet object
trajectoryset A TrajectorySet object coupled to the particleset

Value

A ParticleSet object with an additional column with the trajectory IDs

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2015

Examples

```
data(candidate.platelets)
trajs <- trajectories(candidate.platelets)
matchTrajToParticles(candidate.platelets, trajs)
```

MesenteriumSubset *A sample Frames object*

Description

The sample Frames object is constituted by a subset of a time-lapse intravital microscopy imaging dataset. Green channel marks leukocytes, red channel focuses on blood platelets. 20 frames are provided in this subset. Images are kindly provided by Sven Jaeckel (<Sven.Jaeckel@unimedizin-mainz.de>).

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

normalizeFrames *Normalize the values of a Frames object*

Description

Applies a transformation to the Frames object in a way that the intensities throughout the acquisition are normalized overall in term of pixel values sums. It can be used to compensate for example a global change in the illumination values, e.g. due to changed acquisition conditions in experiments that span long timescales.

Usage

```
normalizeFrames(frames, normFun = "median")
```

Arguments

frames	A Frames object to normalize
normFun	The normalization function chosen. Can be one of mean or median

Value

A Frames object with normalized pixel values.

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data(MesenteriumSubset)
normalizeFrames(MesenteriumSubset, normFun="median")
```

particles *Extracts particles from the images of a Frames object.*

Description

Extracts particles from the images of a Frames object.

Usage

```
particles(raw.frames, binary.frames = NULL, channel = NULL,
         BPPARAM = bpparam())
```

Arguments

raw.frames	A Frames object with the raw images (mandatory)
binary.frames	A Frames object with preprocessed images (optional, if not provided gets produced with standard default parameters)
channel	Character string. The channel to perform the operations on. Can be red, green or blue
BPPARAM	a MulticoreParam object, used to control the performances inside the BiocParallel call to process frames in parallel by taking advantage of the computing infrastructure available

Value

A ParticleSet object, containing all detected particles for each frame

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2015

Examples

```
data("MesenteriumSubset")
```

ParticleSet-class *ParticleSet class*

Description

S4 class for storing information on particles detected in distinct frames.

Slots

.Data A list storing the information for the particles
channel A character vector, can be 'red', 'green', or 'blue'. It refers to which channel the particles were detected

penaltyFunctionGenerator
Generate a penalty function

Description

A function to generate penalty functions to use while linking particles

Usage

```
penaltyFunctionGenerator(epsilon1 = 0.1, epsilon2 = 2, lambda1 = 1,  
  lambda2 = 1)
```

Arguments

epsilon1	A numeric value, to be used in the formula. Jitter for allowing angular displacements
epsilon2	A numeric value, to be used in the formula. Jitter for allowing spatial displacements
lambda1	A numeric value. Multiplicative factor for the penalty function
lambda2	A numeric value. Multiplicative factor applied to the angular displacement

Value

A function object, to be used as penalty function

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
custom.function <- penaltyFunctionGenerator(epsilon1=0.1,epsilon2=6,lambda1=1.5,lambda2=0)
```

plot.TrajectorySet *3D representation of a TrajectorySet object*

Description

Provides a visual representation of a TrajectorySet object

Usage

```
## S3 method for class TrajectorySet  
plot(x, frames, verbose = FALSE, ...)
```

Arguments

x	A TrajectorySet object
frames	A Frames object, used here to identify the limits of the region of interest
verbose	Logical, whether to provide additional output on the command line
...	Arguments to be passed to methods

Details

Based on the `rgl` library, the function extracts the region of interests from the dimensions of an image of the `Frames` object, and afterwards plots the x-y-time representation of the identified trajectories

Value

`plot.TrajectorySet` returns an invisible `NULL`.

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("MesenteriumSubset")
data("candidate.platelets")
platelets.trajectories <- trajectories(candidate.platelets)
## Not run:
plot(platelets.trajectories, MesenteriumSubset)

## End(Not run)
```

`plot2D.TrajectorySet` *2D projection of a TrajectorySet object*

Description

Provides a bird's eye view of a `TrajectorySet` object on a bidimensional space

Usage

```
plot2D.TrajectorySet(trajectoryset, frames, trajIDs = NULL, addGrid = FALSE,
  verbose = FALSE, ...)
```

Arguments

trajectoryset	A TrajectorySet object
frames	A Frames object, used here to identify the limits of the region of interest
trajIDs	A vector containing the ids of the desired trajectories
addGrid	Logical, add an additional grid to the 2-dimensional plot (visual aid for back-tracking trajectory point locations)
verbose	Logical, whether to provide additional output on the command line
...	Arguments to be passed to methods

Details

Independent from the `rgl` library, the function extracts the region of interests from the dimensions of an image of the Frames object, and afterwards plots the x-y-time representation of the identified trajectories on a 2d plane. It is possible to subset the TrajectorySet object with the IDs of the desired trajectories

Value

`plot2D.TrajectorySet` returns an invisible NULL.

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("MesenteriumSubset")
data("candidate.platelets")
platelets.trajectories <- trajectories(candidate.platelets)
plot2D.TrajectorySet(platelets.trajectories, MesenteriumSubset)
```

`preprocess.Frames` *Preprocessing function for Frames objects*

Description

Frames objects are processed according to the chosen set of parameters. Many of them refer directly to existing EBImage functions, please see the corresponding help for additional information

Usage

```
preprocess.Frames(frames, brush.size = 3, brush.shape = "disc",
  at.offset = 0.15, at.wwidth = 10, at.wheight = 10, kern.size = 3,
  kern.shape = "disc", ws.tolerance = 1, ws.radius = 1,
  displayprocessing = FALSE, ...)
```

Arguments

frames	A Frames object
brush.size	Size in pixels of the brush to be used for initial smoothing (low-pass filtering)
brush.shape	Shape of the brush to be used for initial smoothing (low-pass filtering)
at.offset	Offset to be used in the adaptive thresholding step - see also thresh . As an alternative thresholding method, see also otsu in the EBImage package.
at.width	Width of the window for the adaptive thresholding step - see also thresh . As an alternative thresholding method, see also otsu in the EBImage package.
at.height	Height of the window for the adaptive thresholding step - see also thresh . As an alternative thresholding method, see also otsu in the EBImage package.
kern.size	Size in pixels of the kernel used for morphological operations - e.g., opening, which is an erosion followed by a dilation, and closing which is a dilation followed by an erosion - see also opening , closing
kern.shape	Shape of the kernel used for morphological operations
ws.tolerance	Tolerance allowed in performing the watershed-based segmentation (see also watershed)
ws.radius	Radius for the watershed-based segmentation (see also watershed)
displayprocessing	Logical, whether to display intermediate steps while performing preprocessing. Dismissed currently, it could increase runtime a lot
...	Arguments to be passed to methods

Value

A Frames object, whose frame images are the preprocessed versions of the input images

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("MesenteriumSubset")
preprocess.Frames(channel.Frames(MesenteriumSubset,"red"))
```

read.Frames

Constructor for a Frames object

Description

This function is used to create a Frames object from a vector of image files (or a folder specifying the directory containing them). The number of frames is also specified, as just a subset of the images can be used for this

Usage

```
read.Frames(image.files, nframes = NULL)
```

Arguments

image.files	Vector of strings containing the locations where the (raw) images are to be found, or alternatively, the path to the folder
nframes	Number of frames that will constitute the Frames object

Value

An object of the Frames class, which holds the info on a list of frames, specifying for each the following elements:

image	The Image object containing the image itself
location	The complete path to the location of the original image

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
## see vignette
## Not run: fullData <- read.Frames(image.files = "/path/to/the/directory", nframes = 100)
```

read.particles	<i>Constructor for a ParticleSet object</i>
----------------	---

Description

This function is used to create a ParticleSet object from a vector/list of tab separated text files, each of one containing one line for each particle in the related frame, alongside with its coordinates and if available, the computed features. The number of frames is also specified, as just a subset of the particle lists can be used for this.

Usage

```
read.particles(particle.files, nframes = NULL)
```

Arguments

particle.files	Vector of strings containing the locations where the particle coordinates are to be found, or alternatively, the path to the folder
nframes	Number of frames that will constitute the ParticleSet object

Value

An object of the ParticleSet class

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
## see vignette and export.particles
```

repmat

Function equivalent for MATLAB's repmat - Replicate and tile arrays

Description

A more flexible and stylish alternative to replicate the behaviour of the repmat function of MATLAB

Usage

```
repmat(a, n, m)
```

Arguments

a	The matrix to copy
n	The n value for the tiling
m	The m value for the tiling

Value

Creates a large matrix consisting of an m-by-n tiling of copies of a.

Author(s)

Robin Hankin, 2001

References

<http://cran.r-project.org/doc/contrib/R-and-octave.txt>

rotate.Frames	<i>Rotates all images in a Frames object</i>
---------------	--

Description

Rotation is performed exploiting the rotate function of the EBImage package. Could be automated if support for coordinate/pixel interaction is included

Usage

```
rotate.Frames(frames, angle, testing = FALSE,  
  output.origin = c(dim(frames)[1]/3, dim(frames)[2]/3),  
  output.dim = c(dim(frames)[1] * 1.5, dim(frames)[2] * 1.5))
```

Arguments

frames	A Frames object
angle	The rotation angle (clockwise) specified in degrees
testing	Logical, whether to just test the rotation or to actually perform it. Default set to FALSE
output.origin	A vector of 2 numbers indicating the dimension of the output image, as in the rotate function
output.dim	A vector of 2 numbers indicating the output coordinates of the origin in pixels, as in the rotate function

Value

A Frames object containing the rotated frames

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("MesenteriumSubset")  
rotate.Frames(MesenteriumSubset, angle = 40)
```

select.Frames	<i>Extracts subsets of frames from a Frames object</i>
---------------	--

Description

An input Frames object is subject to subsetting. This function is useful e.g. when the trajectory of interest is presenting gaps (i.e. does not actually include a frame)

Usage

```
select.Frames(frames, framesToKeep = 1, ...)
```

Arguments

frames	A Frames object
framesToKeep	A vector containing the indexes of the frames to keep in the selection
...	Arguments to be passed to methods

Value

A Frames object, composed by the subset of frames of the input Frames

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("MesenteriumSubset")
select.Frames(MesenteriumSubset, framesToKeep = c(1:10, 14:20))
```

select.particles	<i>Performs filtering on a ParticleSet object</i>
------------------	---

Description

According to parameters of interests, such as size, eccentricity/shape, filters out the particles that do not satisfy the indicated requirements

Usage

```
select.particles(particleset, min.area = 1, max.area = 1000)
```

Arguments

particleset	A ParticleSet object. A LinkedParticleSet object can also be provided as input, yet the returned object will be a ParticleSet object that needs to be linked again
min.area	Size in pixels of the minimum area needed to detect the object as a potential particle of interest
max.area	Size in pixels of the maximum area allowed to detect the object as a potential particle of interest

Value

A ParticleSet object

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("candidate.platelets")
selected.platelets <- select.particles(candidate.platelets, min.area = 5)
selected.platelets
```

shinyFlow	<i>Shiny application for exploring the features and parameters provided by flowcatchR</i>
-----------	---

Description

Launches a Shiny Web Application for interactive data exploration. Default data loaded are the frames from the MesenteriumSubset object, custom values can be inserted by typing the location of the data stored in a local folder. The Application is structured in a variety of tabs that mirror the steps in the usual workflow in time-lapse microscopy images. These can allow the user to interactively explore the parameters and their effect in the reactive framework provided by Shiny.

Usage

```
shinyFlow()
```

Value

The Shiny Application is launched in the web browser

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2015

Examples

```
## Not run: shinyFlow()
```

show,Frames-method *Display conveniently a Frames object*

Description

Display conveniently a Frames object

Usage

```
## S4 method for signature Frames  
show(object)
```

Arguments

object A Frames object
... Arguments to be passed to methods

Value

This returns an invisible NULL.

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("MesenteriumSubset")  
print(MesenteriumSubset)
```

show,KinematicsFeatures-method
 Displaying conveniently a KinematicsFeatures object

Description

Displaying conveniently a KinematicsFeatures object

Usage

```
## S4 method for signature KinematicsFeatures  
show(object)
```

Arguments

object A KinematicsFeatures object
... Arguments to be passed to methods

Value

This returns an invisible NULL.

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("candidate.platelets")
platelets.trajectories <- trajectories(candidate.platelets)
traj11features <- kinematics(platelets.trajectories, trajectoryIDs = 11)
print(traj11features)
```

show, KinematicsFeaturesSet-method

Display conveniently a KinematicsFeatureSet object

Description

Display conveniently a KinematicsFeatureSet object

Usage

```
## S4 method for signature KinematicsFeaturesSet
show(object)
```

Arguments

object A KinematicsFeatureSet object
... Arguments to be passed to methods

Value

This returns an invisible NULL.

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("candidate.platelets")
platelets.trajectories <- trajectories(candidate.platelets)
alltrajs.features <- kinematics(platelets.trajectories)
print(alltrajs.features)
```

show,LinkedParticleSet-method

Display conveniently a LinkedParticleSet object

Description

Display conveniently a LinkedParticleSet object

Usage

```
## S4 method for signature LinkedParticleSet
show(object)
```

Arguments

object	A LinkedParticleSet object
...	Arguments to be passed to methods

Value

This returns an invisible NULL.

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("candidate.platelets")
linked.platelets <- link.particles(candidate.platelets,L=26,R=3,epsilon1=0,
epsilon2=0,lambda1=1,lambda2=0,penaltyFunction=penaltyFunctionGenerator(),
include.area=FALSE)
print(linked.platelets)
```

show, ParticleSet-method

Display conveniently a ParticleSet object

Description

Display conveniently a ParticleSet object

Usage

```
## S4 method for signature ParticleSet
show(object)
```

Arguments

object	A ParticleSet object
...	Arguments to be passed to methods

Value

This returns an invisible NULL.

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("candidate.platelets")
print(candidate.platelets)
```

show, TrajectorySet-method

Display conveniently a TrajectorySet object

Description

Display conveniently a TrajectorySet object

Usage

```
## S4 method for signature TrajectorySet
show(object)
```


Arguments

object A TrajectorySet object
 ... Arguments to be passed to methods

Value

This returns an invisible NULL.

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("candidate.platelets")
platelets.trajectories <- trajectories(candidate.platelets)
print(platelets.trajectories)
```

 snap

Snap the features of the closest particle identified

Description

This function combines all classes related to a single experiment in order to deliver a clickable feedback on one of the frames.

Usage

```
snap(raw.frames, binary.frames, particleset, trajectoryset, frameID = 1,
      infocol = "yellow", infocex = 1, showVelocity = FALSE)
```

Arguments

raw.frames A Frames object with the raw frames data
 binary.frames A Frames object with the preprocessed frames data
 particleset A ParticleSet object with the particles data
 trajectoryset A TrajectorySet object with the trajectories data
 frameID The ID of the frame to inspect
 infocol The color to use for plotting the contours and the information on the clicked particle
 infocex The numeric character expansion value as in cex to be used for printing the text on the image
 showVelocity Logical, whether to display additional information on the instantaneous velocity of the particle

Value

An image of the selected frame, rendered in R native graphics, and additionally a list with the coordinates as well as the trajectory ID of the particle closest to the clicked location

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2015

Examples

```
## Not run: data(MesenteriumSubset)
binary.frames <- preprocess.Frames(channel.Frames(MesenteriumSubset,"red"))
particleset <- particles(MesenteriumSubset,binary.frames,"red")
trajectoryset <- trajectories(particleset)
snap(MesenteriumSubset,binary.frames,particleset,trajectoryset,frameID=1)

## End(Not run)
```

toCartesianCoords	<i>Converts polar coordinates to cartesian coordinates</i>
-------------------	--

Description

Conversion from (radius,theta) to (x,y)

Usage

```
toCartesianCoords(Theta, Radius)
```

Arguments

Theta	The Theta angle
Radius	The radius value in polar coordinates

Value

A list containing Theta and Radius, as in polar coordinates

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

toPolarCoords	<i>Converts cartesian coordinates to polar coordinates</i>
---------------	--

Description

Conversion from (x,y) to (radius,theta)

Usage

```
toPolarCoords(x, y)
```

Arguments

x	x coordinate
y	y coordinate

Value

A list containing Theta and Radius, as in polar coordinates

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

trajectories	<i>Generate trajectories</i>
--------------	------------------------------

Description

Generates a TrajectorySet object from a (Linked)ParticleSet

Usage

```
trajectories(particleset, verbose = FALSE, ...)
```

Arguments

particleset	A (Linked)ParticleSet object
verbose	Logical, currently not used - could be introduced for providing additional info on the trajectories
...	Arguments to be passed to methods

Value

A TrajectorySet object

Author(s)

Federico Marini, <marinif@uni-mainz.de>, 2014

Examples

```
data("candidate.platelets")
platelets.trajectories <- trajectories(candidate.platelets)
```

TrajectorySet-class *TrajectorySet class*

Description

S4 class for storing information on the trajectories identified, including whether there were gaps, the number of points, and more

Slots

.Data A list storing the information for the particles

channel A character vector, can be 'red', 'green', or 'blue'. It refers to which channel the particles were detected

Index

add.contours, [3](#)
addParticles, [4](#)
axesInfo, [5](#)

candidate.platelets, [5](#)
channel.Frames, [6](#)
closing, [23](#)
computeMSD, [6](#)
crop.Frames, [7](#)

display, [7](#)

export.Frames, [8](#)
export.particles, [9](#)
extractKinematics.traj, [9](#)

flowcatchR, [10](#)
flowcatchR-package (flowcatchR), [10](#)
Frames, [11](#)
Frames-class, [11](#)

initialize.LinkedParticleSet, [12](#)
inspect.Frames, [12](#)

kinematics, [13](#)
KinematicsFeatures-class, [14](#)
KinematicsFeaturesSet-class, [14](#)

length.Frames, [15](#)
link.particles, [15](#)
LinkedParticleSet-class, [17](#)

matchTrajToParticles, [17](#)
MesenteriumSubset, [18](#)

normalizeFrames, [18](#)

opening, [23](#)
otsu, [23](#)

particles, [19](#)
ParticleSet-class, [19](#)

penaltyFunctionGenerator, [20](#)
plot.TrajectorySet, [20](#)
plot2D.TrajectorySet, [21](#)
preprocess.Frames, [22](#)

read.Frames, [23](#)
read.particles, [24](#)
repmat, [25](#)
rotate.Frames, [26](#)

select.Frames, [27](#)
select.particles, [27](#)
shinyFlow, [28](#)
show, Frames-method, [29](#)
show, KinematicsFeatures-method, [29](#)
show, KinematicsFeaturesSet-method, [30](#)
show, LinkedParticleSet-method, [31](#)
show, ParticleSet-method, [32](#)
show, TrajectorySet-method, [32](#)
snap, [17](#), [33](#)

thresh, [23](#)
toCartesianCoords, [34](#)
toPolarCoords, [35](#)
trajectories, [35](#)
TrajectorySet-class, [36](#)

watershed, [23](#)