

Package ‘chipenrich.data’

April 12, 2018

Title Companion package to chipenrich

Version 2.2.0

Date 2017-10-24

Description Supporting data for the chipenrich package. Includes pre-defined gene sets, gene locus definitions, and mappability estimates.

biocViews ChIPSeq, Epigenetics, FunctionalGenomics, GeneSetEnrichment, HistoneModification, Regression

Depends R (>= 3.4.0)

Imports AnnotationDbi, BiocGenerics, methods, GenomicRanges, GenomeInfoDb, IRanges, readr, rtracklayer, S4Vectors, utils

License GPL-3

Encoding UTF-8

LazyData true

Suggests BiocStyle, devtools, knitr, rmarkdown, roxygen2, testthat, GO.db, org.Dm.eg.db, org.Dr.eg.db, org.Hs.eg.db, org.Mm.eg.db, org.Rn.eg.db, TxDb.Dmelanogaster.UCSC.dm3.ensGene, TxDb.Dmelanogaster.UCSC.dm6.ensGene, TxDb.Drerio.UCSC.danRer10.refGene, TxDb.Hsapiens.UCSC.hg19.knownGene, TxDb.Hsapiens.UCSC.hg38.knownGene, TxDb.Mmusculus.UCSC.mm9.knownGene, TxDb.Mmusculus.UCSC.mm10.knownGene, TxDb.Rnorvegicus.UCSC.rn4.ensGene, TxDb.Rnorvegicus.UCSC.rn5.refGene, TxDb.Rnorvegicus.UCSC.rn6.refGene

VignetteBuilder knitr

RoxygenNote 6.0.1

Maintainer Raymond G. Cavalcante <rcavalca@umich.edu>

NeedsCompilation no

Author Ryan P. Welch [aut, cph],
Chee Lee [aut],
Raymond G. Cavalcante [aut, cre],
Laura J. Scott [ths],
Maureen A. Sartor [ths]

R topics documented:

chipenrich.data	7
GeneSet-class	7
geneset.biocarta_pathway.hsa	8
geneset.biocarta_pathway.mmu	9
geneset.biocarta_pathway.rno	9
geneset.ctd.hsa	10
geneset.cytoband.hsa	10
geneset.drug_bank.hsa	11
geneset.drug_bank.mmu	11
geneset.drug_bank.rno	12
geneset.ehmn_pathway_gene.hsa	12
geneset.ehmn_pathway_gene.mmu	13
geneset.ehmn_pathway_gene.rno	13
geneset.gene_expression.hsa	14
geneset.gene_expression.mmu	14
geneset.GOBP.dme	15
geneset.GOBP.dre	15
geneset.GOBP.hsa	16
geneset.GOBP.mmu	17
geneset.GOBP.rno	17
geneset.GOCC.dme	18
geneset.GOCC.dre	19
geneset.GOCC.hsa	19
geneset.GOCC.mmu	20
geneset.GOCC.rno	21
geneset.GOMF.dme	21
geneset.GOMF.dre	22
geneset.GOMF.hsa	23
geneset.GOMF.mmu	23
geneset.GOMF.rno	24
geneset.hallmark.hsa	25
geneset.immunologic.hsa	25
geneset.kegg_pathway.hsa	26
geneset.kegg_pathway.mmu	27
geneset.kegg_pathway.rno	27
geneset.mesh.hsa	28
geneset.mesh.mmu	28
geneset.mesh.rno	29
geneset.metabolite.hsa	29
geneset.metabolite.mmu	30
geneset.metabolite.rno	30
geneset.microrna.hsa	31
geneset.oncogenic.hsa	31
geneset.panther_pathway.hsa	32
geneset.panther_pathway.mmu	33
geneset.panther_pathway.rno	33
geneset.pfam.hsa	34
geneset.pfam.mmu	34
geneset.pfam.rno	35
geneset.protein_interaction_biogrid.hsa	35

geneset.reactome.dme	36
geneset.reactome.dre	36
geneset.reactome.hsa	37
geneset.reactome.mmu	38
geneset.reactome.rno	38
geneset.transcription_factors.hsa	39
geneset.transcription_factors.mmu	40
geneset.transcription_factors.rno	40
locusdef.danRer10.10kb	41
locusdef.danRer10.10kb_outside	41
locusdef.danRer10.10kb_outside_upstream	42
locusdef.danRer10.1kb	43
locusdef.danRer10.1kb_outside	43
locusdef.danRer10.1kb_outside_upstream	44
locusdef.danRer10.5kb	45
locusdef.danRer10.5kb_outside	45
locusdef.danRer10.5kb_outside_upstream	46
locusdef.danRer10.exon	47
locusdef.danRer10.intron	47
locusdef.danRer10.nearest_gene	48
locusdef.danRer10.nearest_tss	49
locusdef.dm3.10kb	49
locusdef.dm3.10kb_outside	50
locusdef.dm3.10kb_outside_upstream	51
locusdef.dm3.1kb	52
locusdef.dm3.1kb_outside	52
locusdef.dm3.1kb_outside_upstream	53
locusdef.dm3.5kb	54
locusdef.dm3.5kb_outside	54
locusdef.dm3.5kb_outside_upstream	55
locusdef.dm3.exon	56
locusdef.dm3.intron	56
locusdef.dm3.nearest_gene	57
locusdef.dm3.nearest_tss	58
locusdef.dm6.10kb	59
locusdef.dm6.10kb_outside	59
locusdef.dm6.10kb_outside_upstream	60
locusdef.dm6.1kb	61
locusdef.dm6.1kb_outside	61
locusdef.dm6.1kb_outside_upstream	62
locusdef.dm6.5kb	63
locusdef.dm6.5kb_outside	63
locusdef.dm6.5kb_outside_upstream	64
locusdef.dm6.exon	65
locusdef.dm6.intron	65
locusdef.dm6.nearest_gene	66
locusdef.dm6.nearest_tss	67
locusdef.hg19.10kb	68
locusdef.hg19.10kb_outside	68
locusdef.hg19.10kb_outside_upstream	69
locusdef.hg19.1kb	70
locusdef.hg19.1kb_outside	71

locusdef.hg19.1kb_outside_upstream	71
locusdef.hg19.5kb	72
locusdef.hg19.5kb_outside	73
locusdef.hg19.5kb_outside_upstream	73
locusdef.hg19.exon	74
locusdef.hg19.intron	75
locusdef.hg19.nearest_gene	75
locusdef.hg19.nearest_tss	76
locusdef.hg38.10kb	77
locusdef.hg38.10kb_outside	78
locusdef.hg38.10kb_outside_upstream	78
locusdef.hg38.1kb	79
locusdef.hg38.1kb_outside	80
locusdef.hg38.1kb_outside_upstream	80
locusdef.hg38.5kb	81
locusdef.hg38.5kb_outside	82
locusdef.hg38.5kb_outside_upstream	82
locusdef.hg38.exon	83
locusdef.hg38.intron	84
locusdef.hg38.nearest_gene	84
locusdef.hg38.nearest_tss	85
locusdef.mm10.10kb	86
locusdef.mm10.10kb_outside	87
locusdef.mm10.10kb_outside_upstream	87
locusdef.mm10.1kb	88
locusdef.mm10.1kb_outside	89
locusdef.mm10.1kb_outside_upstream	89
locusdef.mm10.5kb	90
locusdef.mm10.5kb_outside	91
locusdef.mm10.5kb_outside_upstream	91
locusdef.mm10.exon	92
locusdef.mm10.intron	93
locusdef.mm10.nearest_gene	93
locusdef.mm10.nearest_tss	94
locusdef.mm9.10kb	95
locusdef.mm9.10kb_outside	96
locusdef.mm9.10kb_outside_upstream	96
locusdef.mm9.1kb	97
locusdef.mm9.1kb_outside	98
locusdef.mm9.1kb_outside_upstream	98
locusdef.mm9.5kb	99
locusdef.mm9.5kb_outside	100
locusdef.mm9.5kb_outside_upstream	100
locusdef.mm9.exon	101
locusdef.mm9.intron	102
locusdef.mm9.nearest_gene	102
locusdef.mm9.nearest_tss	103
locusdef.rn4.10kb	104
locusdef.rn4.10kb_outside	105
locusdef.rn4.10kb_outside_upstream	105
locusdef.rn4.1kb	106
locusdef.rn4.1kb_outside	107

locusdef.rn4.1kb_outside_upstream	107
locusdef.rn4.5kb	108
locusdef.rn4.5kb_outside	109
locusdef.rn4.5kb_outside_upstream	109
locusdef.rn4.exon	110
locusdef.rn4.intron	111
locusdef.rn4.nearest_gene	111
locusdef.rn4.nearest_tss	112
locusdef.rn5.10kb	113
locusdef.rn5.10kb_outside	113
locusdef.rn5.10kb_outside_upstream	114
locusdef.rn5.1kb	115
locusdef.rn5.1kb_outside	115
locusdef.rn5.1kb_outside_upstream	116
locusdef.rn5.5kb	117
locusdef.rn5.5kb_outside	117
locusdef.rn5.5kb_outside_upstream	118
locusdef.rn5.exon	119
locusdef.rn5.intron	119
locusdef.rn5.nearest_gene	120
locusdef.rn5.nearest_tss	121
locusdef.rn6.10kb	121
locusdef.rn6.10kb_outside	122
locusdef.rn6.10kb_outside_upstream	123
locusdef.rn6.1kb	123
locusdef.rn6.1kb_outside	124
locusdef.rn6.1kb_outside_upstream	125
locusdef.rn6.5kb	125
locusdef.rn6.5kb_outside	126
locusdef.rn6.5kb_outside_upstream	127
locusdef.rn6.exon	127
locusdef.rn6.intron	128
locusdef.rn6.nearest_gene	129
locusdef.rn6.nearest_tss	129
LocusDefinition-class	130
mappa.hg19.10kb.100mer	131
mappa.hg19.10kb.24mer	132
mappa.hg19.10kb.36mer	132
mappa.hg19.10kb.40mer	133
mappa.hg19.10kb.50mer	134
mappa.hg19.10kb.75mer	134
mappa.hg19.1kb.100mer	135
mappa.hg19.1kb.24mer	136
mappa.hg19.1kb.36mer	136
mappa.hg19.1kb.40mer	137
mappa.hg19.1kb.50mer	138
mappa.hg19.1kb.75mer	138
mappa.hg19.5kb.100mer	139
mappa.hg19.5kb.24mer	140
mappa.hg19.5kb.36mer	140
mappa.hg19.5kb.40mer	141
mappa.hg19.5kb.50mer	142

mappa.hg19.5kb.75mer	142
mappa.hg19.exon.100mer	143
mappa.hg19.exon.24mer	144
mappa.hg19.exon.36mer	144
mappa.hg19.exon.40mer	145
mappa.hg19.exon.50mer	146
mappa.hg19.exon.75mer	146
mappa.hg19.intron.100mer	147
mappa.hg19.intron.24mer	148
mappa.hg19.intron.36mer	148
mappa.hg19.intron.40mer	149
mappa.hg19.intron.50mer	150
mappa.hg19.intron.75mer	150
mappa.hg19.nearest_gene.100mer	151
mappa.hg19.nearest_gene.24mer	152
mappa.hg19.nearest_gene.36mer	152
mappa.hg19.nearest_gene.40mer	153
mappa.hg19.nearest_gene.50mer	154
mappa.hg19.nearest_gene.75mer	154
mappa.hg19.nearest_tss.100mer	155
mappa.hg19.nearest_tss.24mer	156
mappa.hg19.nearest_tss.36mer	156
mappa.hg19.nearest_tss.40mer	157
mappa.hg19.nearest_tss.50mer	158
mappa.hg19.nearest_tss.75mer	158
mappa.mm9.10kb.100mer	159
mappa.mm9.10kb.36mer	160
mappa.mm9.10kb.40mer	160
mappa.mm9.10kb.50mer	161
mappa.mm9.10kb.75mer	162
mappa.mm9.1kb.100mer	162
mappa.mm9.1kb.36mer	163
mappa.mm9.1kb.40mer	164
mappa.mm9.1kb.50mer	164
mappa.mm9.1kb.75mer	165
mappa.mm9.5kb.100mer	166
mappa.mm9.5kb.36mer	166
mappa.mm9.5kb.40mer	167
mappa.mm9.5kb.50mer	168
mappa.mm9.5kb.75mer	168
mappa.mm9.exon.100mer	169
mappa.mm9.exon.36mer	170
mappa.mm9.exon.40mer	170
mappa.mm9.exon.50mer	171
mappa.mm9.exon.75mer	172
mappa.mm9.intron.100mer	172
mappa.mm9.intron.36mer	173
mappa.mm9.intron.40mer	174
mappa.mm9.intron.50mer	174
mappa.mm9.intron.75mer	175
mappa.mm9.nearest_gene.100mer	176
mappa.mm9.nearest_gene.36mer	176

mappa.mm9.nearest_gene.40mer	177
mappa.mm9.nearest_gene.50mer	178
mappa.mm9.nearest_gene.75mer	178
mappa.mm9.nearest_tss.100mer	179
mappa.mm9.nearest_tss.36mer	180
mappa.mm9.nearest_tss.40mer	180
mappa.mm9.nearest_tss.50mer	181
mappa.mm9.nearest_tss.75mer	182
peaks_E2F4	182
peaks_H3K4me3_GM12878	183
tss.danRer10	184
tss.dm3	184
tss.dm6	185
tss.hg19	185
tss.hg38	186
tss.mm10	186
tss.mm9	187
tss.rn4	187
tss.rn5	188
tss.rn6	188

Index	189
--------------	------------

chipenrich.data	<i>chipenrich.data: Data for chipenrich: gene set enrichment analysis for ChIP-seq data</i>
-----------------	---

Description

Supporting data for the chipenrich package. Includes pre-defined gene sets, gene locus definitions, and mappability estimates.

GeneSet-class	<i>Class "GeneSet"</i>
---------------	------------------------

Description

Class for storing sets of genes and their corresponding metadata.

Objects from the Class

Objects can be created by calls of the form `new("GeneSet")`.

These objects are used internally by the chipenrich package and users will not likely need to create these.

Slots

set.gene: Object of class "environment". Maps from geneset IDs to lists of Entrez gene IDs.
type: Object of class "character". The formal name for this collection of genesets.
set.name: Object of class "environment". Maps from geneset IDs to their descriptions/names.
all.genes: Object of class "character". A set of all genes present across every geneset.
organism: Object of class "character". Organism code for gene IDs.
dburl: Object of class "character". Web URL for this collection of genesets.

Note

Not typically accessed by the user - this is used internally by the chipenrich package.

Author(s)

Ryan Welch <welchr@umich.edu>

Examples

```

# Show information about class.
showClass("GeneSet")

# What is stored inside a geneset object?
data("geneset.metabolite.hsa");
str(geneset.metabolite.hsa);

# How are the mappings from geneset IDs to gene IDs stored?
ls.str(geneset.metabolite.hsa@set.gene);

```

geneset.biocarta_pathway.hsa

geneset.biocarta_pathway.hsa genesets for BioCarta

Description

BioCarta (biocarta_pathway) genesets. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 18:46:04 2017.

Usage

```
geneset.biocarta_pathway.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

https://cgap.nci.nih.gov/Pathways/BioCarta_Pathways

geneset.biocarta_pathway.mmu
geneset.biocarta_pathway.mmu

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.biocarta_pathway.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.biocarta_pathway.rno
geneset.biocarta_pathway.rno

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.biocarta_pathway.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.ctd.hsa *geneset.ctd.hsa* genesets for Comparative Toxicogenomics Database

Description

Comparative Toxicogenomics Database (ctd) genesets. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 18:46:11 2017.

Usage

```
geneset.ctd.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

```
http://ctdbase.org
```

geneset.cytoband.hsa *geneset.cytoband.hsa*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.cytoband.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.drug_bank.hsa *geneset.drug_bank.hsa* genesets for DrugBank

Description

DrugBank (drug_bank) genesets. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 18:46:13 2017.

Usage

```
geneset.drug_bank.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

<https://www.drugbank.ca>

geneset.drug_bank.mmu *geneset.drug_bank.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.drug_bank.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.drug_bank.rno  geneset.drug_bank.rno
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.drug_bank.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.ehmn_pathway_gene.hsa  
  geneset.ehmn_pathway_gene.hsa
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.ehmn_pathway_gene.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.ehmn_pathway_gene.mmu  
geneset.ehmn_pathway_gene.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.ehmn_pathway_gene.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.ehmn_pathway_gene.rno  
geneset.ehmn_pathway_gene.rno
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.ehmn_pathway_gene.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.gene_expression.hsa`
geneset.gene_expression.hsa

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.gene_expression.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.gene_expression.mmu`
geneset.gene_expression.mmu

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.gene_expression.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.GOBP.dme	<i>geneset.GOBP.dme genesets for Drosophila melanogaster</i>
------------------	--

Description

Gene Ontology Biological Process (GOBP) genesets for *Drosophila melanogaster*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:24:38 2017.

Usage

```
geneset.GOBP.dme
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dm.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOBP.dre	<i>geneset.GOBP.dre genesets for Danio rerio</i>
------------------	--

Description

Gene Ontology Biological Process (GOBP) genesets for *Danio rerio*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:25:08 2017.

Usage

```
geneset.GOBP.dre
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dr.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOBP.hsa

geneset.GOBP.hsa genesets for Homo sapiens

Description

Gene Ontology Biological Process (GOBP) genesets for Homo sapiens. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:22:22 2017.

Usage

geneset.GOBP.hsa

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Hs.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOBP.mmu *geneset.GOBP.mmu genesets for Mus musculus*

Description

Gene Ontology Biological Process (GOBP) genesets for *Mus musculus*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:23:23 2017.

Usage

geneset.GOBP.mmu

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Mm.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOBP.rno *geneset.GOBP.rno genesets for Rattus norvegicus*

Description

Gene Ontology Biological Process (GOBP) genesets for *Rattus norvegicus*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:24:10 2017.

Usage

geneset.GOBP.rno

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Rn.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOCC.dme

geneset.GOCC.dme genesets for Drosophila melanogaster

Description

Gene Ontology Cellular Component (GOCC) genesets for Drosophila melanogaster. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:24:38 2017.

Usage

geneset.GOCC.dme

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dm.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOCC.dre *geneset.GOCC.dre genesets for Danio rerio*

Description

Gene Ontology Cellular Component (GOCC) genesets for Danio rerio. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:25:08 2017.

Usage

geneset.GOCC.dre

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dr.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOCC.hsa *geneset.GOCC.hsa genesets for Homo sapiens*

Description

Gene Ontology Cellular Component (GOCC) genesets for Homo sapiens. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:22:22 2017.

Usage

geneset.GOCC.hsa

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Hs.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOCC.mmu

geneset.GOCC.mmu genesets for Mus musculus

Description

Gene Ontology Cellular Component (GOCC) genesets for Mus musculus. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:23:23 2017.

Usage

geneset.GOCC.mmu

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Mm.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOCC.rno *geneset.GOCC.rno genesets for Rattus norvegicus*

Description

Gene Ontology Cellular Component (GOCC) genesets for *Rattus norvegicus*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:24:10 2017.

Usage

geneset.GOCC.rno

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Rn.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOMF.dme *geneset.GOMF.dme genesets for Drosophila melanogaster*

Description

Gene Ontology Molecular Function (GOMF) genesets for *Drosophila melanogaster*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:24:38 2017.

Usage

geneset.GOMF.dme

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dm.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOMF.dre *geneset.GOMF.dre genesets for Danio rerio*

Description

Gene Ontology Molecular Function (GOMF) genesets for Danio rerio. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:25:08 2017.

Usage

geneset.GOMF.dre

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dr.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOMF.hsa *geneset.GOMF.hsa genesets for Homo sapiens*

Description

Gene Ontology Molecular Function (GOMF) genesets for Homo sapiens. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:22:22 2017.

Usage

geneset.GOMF.hsa

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Hs.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOMF.mmu *geneset.GOMF.mmu genesets for Mus musculus*

Description

Gene Ontology Molecular Function (GOMF) genesets for Mus musculus. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:23:23 2017.

Usage

geneset.GOMF.mmu

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Mm.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOMF.rno	<i>geneset.GOMF.rno genesets for Rattus norvegicus</i>
------------------	--

Description

Gene Ontology Molecular Function (GOMF) genesets for Rattus norvegicus. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:24:10 2017.

Usage

geneset.GOMF.rno

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Rn.eg.db_3.4.2 and GO.db_3.4.2

geneset.hallmark.hsa *geneset.hallmark.hsa genesets for Hallmark (MSigDB)*

Description

Hallmark (MSigDB) (hallmark) genesets. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 18:46:15 2017.

Usage

geneset.hallmark.hsa

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

<http://software.broadinstitute.org/gsea/msigdb/collections.jsp#H>

geneset.immunologic.hsa

geneset.immunologic.hsa genesets for Immunologic Signatures (MSigDB)

Description

Immunologic Signatures (MSigDB) (immunologic) genesets. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 18:46:45 2017.

Usage

geneset.immunologic.hsa

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

<http://software.broadinstitute.org/gsea/msigdb/collections.jsp#C7>

geneset.kegg_pathway.hsa

geneset.kegg_pathway.hsa genesets for KEGG Pathways

Description

KEGG Pathways (kegg_pathway) genesets. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 18:46:53 2017.

Usage

geneset.kegg_pathway.hsa

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

<http://kegg.jp>

```
geneset.kegg_pathway.mmu  
  geneset.kegg_pathway.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.kegg_pathway.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.kegg_pathway.rno  
  geneset.kegg_pathway.rno
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.kegg_pathway.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.mesh.hsa *geneset.mesh.hsa*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mesh.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.mesh.mmu *geneset.mesh.mmu*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mesh.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.mesh.rno *geneset.mesh.rno*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mesh.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.metabolite.hsa
geneset.metabolite.hsa

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.metabolite.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.metabolite.mmu

geneset.metabolite.mmu

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.metabolite.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.metabolite.rno

geneset.metabolite.rno

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.metabolite.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.microrna.hsa *geneset.microrna.hsa genesets for MicroRNA Targets (MSigDB)*

Description

MicroRNA Targets (MSigDB) (microrna) genesets. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 18:46:56 2017.

Usage

geneset.microrna.hsa

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

<http://software.broadinstitute.org/gsea/msigdb/collections.jsp#C3>

geneset.oncogenic.hsa *geneset.oncogenic.hsa genesets for Oncogenic Signatures (MSigDB)*

Description

Oncogenic Signatures (MSigDB) (oncogenic) genesets. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 18:47:23 2017.

Usage

geneset.oncogenic.hsa

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

<http://software.broadinstitute.org/gsea/msigdb/collections.jsp#C6>

`geneset.panther_pathway.hsa`
geneset.panther_pathway.hsa

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.panther_pathway.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.panther_pathway.mmu  
geneset.panther_pathway.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.panther_pathway.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.panther_pathway.rno  
geneset.panther_pathway.rno
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.panther_pathway.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.pfam.hsa *geneset.pfam.hsa* genesets for Pfam

Description

Pfam (pfam) genesets. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 18:47:28 2017.

Usage

geneset.pfam.hsa

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

<http://pfam.xfam.org>

geneset.pfam.mmu *geneset.pfam.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

data(geneset.pfam.mmu)

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.pfam.rno      geneset.pfam.rno
```

Description

GeneSet object which stores information about sets of genes.
 These objects are used internally by the chipenrich package.

Usage

```
data(geneset.pfam.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.protein_interaction_biogrid.hsa
      geneset.protein_interaction_biogrid.hsa genesets for BioGRID Protein Interactions
```

Description

BioGRID Protein Interactions (protein_interaction_biogrid) genesets. All genesets are required to have ≥ 10 Entrez IDs. Built on Tue Oct 24 16:05:53 2017.

Usage

```
geneset.protein_interaction_biogrid.hsa
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

<https://thebiogrid.org>

geneset.reactome.dme *geneset.reactome.dme genesets for Drosophila melanogaster*

Description

Reactome genesets for Drosophila melanogaster. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Mar 20 15:14:03 2017.

Usage

geneset.reactome.dme

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. Reactome.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. R-HSA-109688), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://www.reactome.org/download/current/NCBI2Reactome_All_Levels.txt downloaded on 2017-03-19

geneset.reactome.dre *geneset.reactome.dre genesets for Danio rerio*

Description

Reactome genesets for Danio rerio. All genesets are required to have ≥ 10 Entrez IDs. Built on Tue Mar 28 13:03:21 2017.

Usage

geneset.reactome.dre

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. Reactome.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. R-HSA-109688), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://www.reactome.org/download/current/NCBI2Reactome_All_Levels.txt downloaded on 2017-03-19

geneset.reactome.hsa *geneset.reactome.hsa genesets for Homo sapiens*

Description

Reactome genesets for Homo sapiens. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Mar 20 15:13:45 2017.

Usage

geneset.reactome.hsa

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. Reactome.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. R-HSA-109688), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://www.reactome.org/download/current/NCBI2Reactome_All_Levels.txt downloaded on 2017-03-19

geneset.reactome.mmu *geneset.reactome.mmu genesets for Mus musculus*

Description

Reactome genesets for *Mus musculus*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Mar 20 15:13:55 2017.

Usage

geneset.reactome.mmu

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. Reactome.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. R-HSA-109688), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://www.reactome.org/download/current/NCBI2Reactome_All_Levels.txt downloaded on 2017-03-19

geneset.reactome.rno *geneset.reactome.rno genesets for Rattus norvegicus*

Description

Reactome genesets for *Rattus norvegicus*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Mar 20 15:13:59 2017.

Usage

geneset.reactome.rno

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. Reactome.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. R-HSA-109688), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://www.reactome.org/download/current/NCBI2Reactome_All_Levels.txt downloaded on 2017-03-19

geneset.transcription_factors.hsa

geneset.transcription_factors.hsa genesets for Transcription Factor Targets (MSigDB)

Description

Transcription Factor Targets (MSigDB) (transcription_factors) genesets. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 18:47:33 2017.

Usage

geneset.transcription_factors.hsa

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

<http://software.broadinstitute.org/gsea/msigdb/collections.jsp#C3>

```
geneset.transcription_factors.mmu  
geneset.transcription_factors.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.transcription_factors.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.transcription_factors.rno  
geneset.transcription_factors.rno
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.transcription_factors.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

locusdef.danRer10.10kb

locusdef.danRer10.10kb locus definition

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

locusdef.danRer10.10kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Tue Mar 28 12:56:08 2017.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.0 and org.Dr.eg.db_3.4.0.

locusdef.danRer10.10kb_outside

locusdef.danRer10.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.danRer10.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Tue Mar 28 12:56:09 2017.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.0 and org.Dr.eg.db_3.4.0.

locusdef.danRer10.10kb_outside_upstream

locusdef.danRer10.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.danRer10.10kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Tue Mar 28 12:56:08 2017.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.0 and org.Dr.eg.db_3.4.0.

locusdef.danRer10.1kb *locusdef.danRer10.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

locusdef.danRer10.1kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Tue Mar 28 12:56:06 2017.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.0 and org.Dr.eg.db_3.4.0.

locusdef.danRer10.1kb_outside
locusdef.danRer10.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.danRer10.1kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Tue Mar 28 12:56:07 2017.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.0 and org.Dr.eg.db_3.4.0.

locusdef.danRer10.1kb_outside_upstream

locusdef.danRer10.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.danRer10.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Tue Mar 28 12:56:06 2017.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.0 and org.Dr.eg.db_3.4.0.

locusdef.danRer10.5kb *locusdef.danRer10.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.danRer10.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Tue Mar 28 12:56:07 2017.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.0 and org.Dr.eg.db_3.4.0.

locusdef.danRer10.5kb_outside

locusdef.danRer10.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.danRer10.5kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Tue Mar 28 12:56:08 2017.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.0 and org.Dr.eg.db_3.4.0.

locusdef.danRer10.5kb_outside_upstream

locusdef.danRer10.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.danRer10.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Tue Mar 28 12:56:07 2017.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.0 and org.Dr.eg.db_3.4.0.

`locusdef.danRer10.exon`*locusdef.danRer10.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage`locusdef.danRer10.exon`**Format**

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `danRer10`.

organism A character indicating the organism name. In this case, `Danio rerio`.

Details

Built on Tue Mar 28 12:56:04 2017.

Source

R packages: `TxDb.Drerio.UCSC.danRer10.refGene_3.4.0` and `org.Dr.eg.db_3.4.0`.

`locusdef.danRer10.intron`*locusdef.danRer10.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage`locusdef.danRer10.intron`

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Tue Mar 28 12:56:06 2017.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.0 and org.Dr.eg.db_3.4.0.

locusdef.danRer10.nearest_gene

locusdef.danRer10.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

```
locusdef.danRer10.nearest_gene
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Tue Mar 28 12:56:02 2017.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.0 and org.Dr.eg.db_3.4.0.

locusdef.danRer10.nearest_tss

locusdef.danRer10.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.danRer10.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Tue Mar 28 12:56:02 2017.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.0 and org.Dr.eg.db_3.4.0.

locusdef.dm3.10kb

locusdef.dm3.10kb locus definition

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.dm3.10kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:03 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

locusdef.dm3.10kb_outside

locusdef.dm3.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.dm3.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:03 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

locusdef.dm3.10kb_outside_upstream

locusdef.dm3.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.dm3.10kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:03 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

locusdef.dm3.1kb *locusdef.dm3.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

locusdef.dm3.1kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:01 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

locusdef.dm3.1kb_outside *locusdef.dm3.1kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.dm3.1kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:02 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

locusdef.dm3.1kb_outside_upstream

locusdef.dm3.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.dm3.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:02 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

locusdef.dm3.5kb *locusdef.dm3.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.dm3.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:02 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

locusdef.dm3.5kb_outside *locusdef.dm3.5kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.dm3.5kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:02 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

locusdef.dm3.5kb_outside_upstream

locusdef.dm3.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.dm3.5kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:02 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

locusdef.dm3.exon *locusdef.dm3.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

locusdef.dm3.exon

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:00 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

locusdef.dm3.intron *locusdef.dm3.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

locusdef.dm3.intron

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:01 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

locusdef.dm3.nearest_gene

locusdef.dm3.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.dm3.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:07:59 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

locusdef.dm3.nearest_tss

locusdef.dm3.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

locusdef.dm3.nearest_tss

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:07:59 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

locusdef.dm6.10kb *locusdef.dm6.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

locusdef.dm6.10kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, *Drosophila melanogaster*.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:40 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

locusdef.dm6.10kb_outside *locusdef.dm6.10kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.dm6.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:40 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

locusdef.dm6.10kb_outside_upstream

locusdef.dm6.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.dm6.10kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:40 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

locusdef.dm6.1kb *locusdef.dm6.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

locusdef.dm6.1kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:39 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

locusdef.dm6.1kb_outside *locusdef.dm6.1kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.dm6.1kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:39 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

locusdef.dm6.1kb_outside_upstream

locusdef.dm6.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.dm6.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:39 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

locusdef.dm6.5kb *locusdef.dm6.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.dm6.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:40 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

locusdef.dm6.5kb_outside *locusdef.dm6.5kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.dm6.5kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:40 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

locusdef.dm6.5kb_outside_upstream

locusdef.dm6.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.dm6.5kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:40 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

locusdef.dm6.exon *locusdef.dm6.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

locusdef.dm6.exon

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:38 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

locusdef.dm6.intron *locusdef.dm6.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

locusdef.dm6.intron

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:39 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

locusdef.dm6.nearest_gene

locusdef.dm6.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.dm6.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:37 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

locusdef.dm6.nearest_tss

locusdef.dm6.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.dm6.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:08:37 2017.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

locusdef.hg19.10kb *locusdef.hg19.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

locusdef.hg19.10kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:52:19 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annots and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Ent

locusdef.hg19.10kb_outside *locusdef.hg19.10kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.hg19.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:52:20 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE

resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annoata and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Ent

locusdef.hg19.10kb_outside_upstream

locusdef.hg19.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.hg19.10kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:52:19 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annots and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entrez

locusdef.hg19.1kb *locusdef.hg19.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

locusdef.hg19.1kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:52:15 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annots and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Entrez

locusdef.hg19.1kb_outside

locusdef.hg19.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.hg19.1kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:52:16 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Ent

locusdef.hg19.1kb_outside_upstream

locusdef.hg19.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.hg19.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:52:15 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annots and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Ent

locusdef.hg19.5kb *locusdef.hg19.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.hg19.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:52:17 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annots and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Ent

locusdef.hg19.5kb_outside

locusdef.hg19.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.hg19.5kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:52:18 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Ent

locusdef.hg19.5kb_outside_upstream

locusdef.hg19.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.hg19.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:52:17 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Ent

locusdef.hg19.exon *locusdef.hg19.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

locusdef.hg19.exon

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:52:12 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Ent

locusdef.hg19.intron *locusdef.hg19.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

locusdef.hg19.intron

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:52:14 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annots and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Ent

locusdef.hg19.nearest_gene
locusdef.hg19.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.hg19.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:52:10 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE

resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annota and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Ent

locusdef.hg19.nearest_tss

locusdef.hg19.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

locusdef.hg19.nearest_tss

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:52:09 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.anno and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Ent

locusdef.hg38.10kb *locusdef.hg38.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

locusdef.hg38.10kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:56:36 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.10kb_outside

locusdef.hg38.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.hg38.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:56:37 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.10kb_outside_upstream

locusdef.hg38.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.hg38.10kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:56:36 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.1kb *locusdef.hg38.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

locusdef.hg38.1kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:56:32 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.1kb_outside

locusdef.hg38.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.hg38.1kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:56:34 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.1kb_outside_upstream

locusdef.hg38.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.hg38.1kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:56:33 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.5kb *locusdef.hg38.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.hg38.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:56:34 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.5kb_outside

locusdef.hg38.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.hg38.5kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:56:36 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.5kb_outside_upstream

locusdef.hg38.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.hg38.5kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:56:35 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.exon *locusdef.hg38.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

locusdef.hg38.exon

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:56:29 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.intron *locusdef.hg38.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

locusdef.hg38.intron

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:56:31 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.nearest_gene
locusdef.hg38.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.hg38.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:56:27 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.nearest_tss

locusdef.hg38.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.hg38.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Sat Mar 18 12:56:26 2017.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.mm10.10kb *locusdef.mm10.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

locusdef.mm10.10kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 13:06:22 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.10kb_outside

locusdef.mm10.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.mm10.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 13:06:23 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.10kb_outside_upstream

locusdef.mm10.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.mm10.10kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 13:06:22 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.1kb *locusdef.mm10.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.mm10.1kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:58:42 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

`locusdef.mm10.1kb_outside`*locusdef.mm10.1kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage`locusdef.mm10.1kb_outside`**Format**

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `mm10`.

organism A character indicating the organism name. In this case, `Mus musculus`.

Details

Built on Sat Mar 18 13:06:19 2017.

Source

R packages: `TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0` and `org.Mm.eg.db_3.4.0`. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

`locusdef.mm10.1kb_outside_upstream`*locusdef.mm10.1kb_outside_upstream locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage`locusdef.mm10.1kb_outside_upstream`

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:58:42 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.5kb *locusdef.mm10.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.mm10.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 13:06:20 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

`locusdef.mm10.5kb_outside`*locusdef.mm10.5kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage`locusdef.mm10.5kb_outside`**Format**

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `mm10`.

organism A character indicating the organism name. In this case, `Mus musculus`.

Details

Built on Sat Mar 18 13:06:21 2017.

Source

R packages: `TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0` and `org.Mm.eg.db_3.4.0`. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

`locusdef.mm10.5kb_outside_upstream`*locusdef.mm10.5kb_outside_upstream locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage`locusdef.mm10.5kb_outside_upstream`

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 13:06:20 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.exon *locusdef.mm10.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

locusdef.mm10.exon

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:58:40 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.intron *locusdef.mm10.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

locusdef.mm10.intron

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:58:41 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.nearest_gene
locusdef.mm10.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.mm10.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:58:37 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.nearest_tss

locusdef.mm10.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

locusdef.mm10.nearest_tss

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:58:37 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm9.10kb *locusdef.mm9.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

locusdef.mm9.10kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:57:38 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.10kb_outside

locusdef.mm9.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.mm9.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:57:38 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.10kb_outside_upstream

locusdef.mm9.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.mm9.10kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:57:38 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.1kb	<i>locusdef.mm9.1kb locus definition</i>
------------------	--

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.mm9.1kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:57:35 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.1kb_outside

locusdef.mm9.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.mm9.1kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:57:36 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.1kb_outside_upstream

locusdef.mm9.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.mm9.1kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:57:35 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.5kb	<i>locusdef.mm9.5kb locus definition</i>
------------------	--

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.mm9.5kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:57:36 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.5kb_outside

locusdef.mm9.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.mm9.5kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, *Mus musculus*.

Details

Built on Sat Mar 18 12:57:37 2017.

Source

R packages: `TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2` and `org.Mm.eg.db_3.4.0`. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.5kb_outside_upstream

locusdef.mm9.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.mm9.5kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:57:37 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.exon	<i>locusdef.mm9.exon locus definition</i>
-------------------	---

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.mm9.exon
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:57:32 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.intron *locusdef.mm9.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

locusdef.mm9.intron

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:57:34 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.nearest_gene
 locusdef.mm9.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.mm9.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:57:30 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.nearest_tss

locusdef.mm9.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.mm9.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Sat Mar 18 12:57:30 2017.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.rn4.10kb *locusdef.rn4.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

locusdef.rn4.10kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:06:49 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.4.0.

locusdef.rn4.10kb_outside

locusdef.rn4.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn4.10kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn4`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

For the `rn4` genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:06:50 2017.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2` and `org.Rn.eg.db_3.4.0`.

locusdef.rn4.10kb_outside_upstream

locusdef.rn4.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn4.10kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:06:50 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.4.0.

locusdef.rn4.1kb *locusdef.rn4.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

locusdef.rn4.1kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:06:47 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.4.0.

`locusdef.rn4.1kb_outside`*locusdef.rn4.1kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage`locusdef.rn4.1kb_outside`**Format**

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn4`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

For the `rn4` genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:06:48 2017.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2` and `org.Rn.eg.db_3.4.0`.

`locusdef.rn4.1kb_outside_upstream`*locusdef.rn4.1kb_outside_upstream locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage`locusdef.rn4.1kb_outside_upstream`

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:06:48 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.4.0.

locusdef.rn4.5kb *locusdef.rn4.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.rn4.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:06:48 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.4.0.

`locusdef.rn4.5kb_outside`*locusdef.rn4.5kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage`locusdef.rn4.5kb_outside`**Format**

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn4`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

For the `rn4` genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:06:49 2017.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2` and `org.Rn.eg.db_3.4.0`.

`locusdef.rn4.5kb_outside_upstream`*locusdef.rn4.5kb_outside_upstream locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage`locusdef.rn4.5kb_outside_upstream`

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:06:49 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.4.0.

locusdef.rn4.exon	<i>locusdef.rn4.exon locus definition</i>
-------------------	---

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

locusdef.rn4.exon

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:06:46 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.4.0.

locusdef.rn4.intron *locusdef.rn4.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

locusdef.rn4.intron

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:06:47 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.4.0.

locusdef.rn4.nearest_gene
 locusdef.rn4.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.rn4.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:06:44 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.4.0.

locusdef.rn4.nearest_tss

locusdef.rn4.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

locusdef.rn4.nearest_tss

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Sat Mar 18 13:06:44 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.4.0.

locusdef.rn5.10kb *locusdef.rn5.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

locusdef.rn5.10kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:12 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn5.10kb_outside *locusdef.rn5.10kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.rn5.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:13 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn5.10kb_outside_upstream

locusdef.rn5.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn5.10kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:12 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn5.1kb *locusdef.rn5.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

locusdef.rn5.1kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:10 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn5.1kb_outside
locusdef.rn5.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.rn5.1kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:11 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn5.1kb_outside_upstream

locusdef.rn5.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.rn5.1kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:10 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn5.5kb *locusdef.rn5.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.rn5.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:11 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn5.5kb_outside
locusdef.rn5.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.rn5.5kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:12 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn5.5kb_outside_upstream

locusdef.rn5.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn5.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:11 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn5.exon *locusdef.rn5.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

locusdef.rn5.exon

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:08 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn5.intron *locusdef.rn5.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

locusdef.rn5.intron

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:09 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn5.nearest_gene

locusdef.rn5.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.rn5.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:06 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

`locusdef.rn5.nearest_tss`*locusdef.rn5.nearest_tss locus definition*

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage`locusdef.rn5.nearest_tss`**Format**

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn5`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Sat Mar 18 13:07:06 2017.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0` and `org.Rn.eg.db_3.4.0`.

`locusdef.rn6.10kb`*locusdef.rn6.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage`locusdef.rn6.10kb`

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:32 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn6.10kb_outside

locusdef.rn6.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.rn6.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:33 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn6.10kb_outside_upstream

locusdef.rn6.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn6.10kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:32 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn6.1kb

locusdef.rn6.1kb locus definition

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.rn6.1kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:30 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn6.1kb_outside

locusdef.rn6.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.rn6.1kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:31 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

`locusdef.rn6.1kb_outside_upstream`*locusdef.rn6.1kb_outside_upstream locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage`locusdef.rn6.1kb_outside_upstream`**Format**

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn6`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Sat Mar 18 13:07:30 2017.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0` and `org.Rn.eg.db_3.4.0`.

`locusdef.rn6.5kb`*locusdef.rn6.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage`locusdef.rn6.5kb`

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:31 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn6.5kb_outside

locusdef.rn6.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.rn6.5kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:32 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

`locusdef.rn6.5kb_outside_upstream`*locusdef.rn6.5kb_outside_upstream locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage`locusdef.rn6.5kb_outside_upstream`**Format**

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn6`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Sat Mar 18 13:07:31 2017.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0` and `org.Rn.eg.db_3.4.0`.

`locusdef.rn6.exon`*locusdef.rn6.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage`locusdef.rn6.exon`

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:28 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn6.intron *locusdef.rn6.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.rn6.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:30 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn6.nearest_gene
locusdef.rn6.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.rn6.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:26 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

locusdef.rn6.nearest_tss
locusdef.rn6.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

locusdef.rn6.nearest_tss

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Sat Mar 18 13:07:26 2017.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

LocusDefinition-class *Class "LocusDefinition"*

Description

A storage class representing gene locus definitions and their corresponding metadata.

Objects from the Class

Objects can be created by calls of the form `new("LocusDefinition")`. These objects are used internally by the chipenrich package and users will not likely need to create these.

Slots

dframe: Object of class "data.frame". Each row represents a locus for a particular geneid.

granges: Object of class "GenomicRanges". Locus definitions stored as a GenomicRanges object.

genome.build: Object of class "character". Genome build these definitions were generated from.

organism: Object of class "character". Organism code.

Note

Not typically accessed by the user - this is used internally by the chipenrich package.

Author(s)

Ryan Welch <welchr@umich.edu>

Examples

```
# Show info about the class.
showClass("LocusDefinition");

# Example of what a locus definition object looks like.
data(locusdef.mm9.nearest_tss);
str(locusdef.mm9.nearest_tss);
```

```
mappa.hg19.10kb.100mer
      mappa.hg19.10kb.100mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb.100mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb.24mer *mappa.hg19.10kb.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.10kb.24mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb.36mer *mappa.hg19.10kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.10kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.10kb.40mer` *mappa.hg19.10kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb.50mer *mappa.hg19.10kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.10kb.50mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb.75mer *mappa.hg19.10kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.10kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.1kb.100mer` *mappa.hg19.1kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.1kb.24mer *mappa.hg19.1kb.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.1kb.24mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.1kb.36mer *mappa.hg19.1kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.1kb.36mer)
```


Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.1kb.40mer` *mappa.hg19.1kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.1kb.50mer *mappa.hg19.1kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.1kb.50mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.1kb.75mer *mappa.hg19.1kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.1kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.5kb.100mer` *mappa.hg19.5kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.5kb.24mer *mappa.hg19.5kb.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.24mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.5kb.36mer *mappa.hg19.5kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.5kb.40mer` *mappa.hg19.5kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.5kb.50mer *mappa.hg19.5kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.50mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.5kb.75mer *mappa.hg19.5kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.100mer

mappa.hg19.exon.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.24mer *mappa.hg19.exon.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.36mer *mappa.hg19.exon.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.36mer)
```


Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.40mer *mappa.hg19.exon.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.exon.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.50mer *mappa.hg19.exon.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.50mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.75mer *mappa.hg19.exon.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.intron.100mer

mappa.hg19.intron.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.intron.24mer
mappa.hg19.intron.24mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.24mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.intron.36mer
mappa.hg19.intron.36mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.intron.40mer`

mappa.hg19.intron.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.intron.50mer
mappa.hg19.intron.50mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.50mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.intron.75mer
mappa.hg19.intron.75mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_gene.100mer
mappa.hg19.nearest_gene.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.nearest_gene.24mer  
mappa.hg19.nearest_gene.24mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.24mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.nearest_gene.36mer  
mappa.hg19.nearest_gene.36mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.36mer)
```


Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_gene.40mer
mappa.hg19.nearest_gene.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.nearest_gene.50mer  
mappa.hg19.nearest_gene.50mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.50mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.nearest_gene.75mer  
mappa.hg19.nearest_gene.75mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.100mer
mappa.hg19.nearest_tss.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.24mer
mappa.hg19.nearest_tss.24mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.24mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.36mer
mappa.hg19.nearest_tss.36mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.40mer
mappa.hg19.nearest_tss.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.50mer
mappa.hg19.nearest_tss.50mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.50mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.75mer
mappa.hg19.nearest_tss.75mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.10kb.100mer` *mappa.mm9.10kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.10kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb.36mer *mappa.mm9.10kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.10kb.36mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb.40mer *mappa.mm9.10kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.10kb.40mer)
```


Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.10kb.50mer` *mappa.mm9.10kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.10kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb.75mer *mappa.mm9.10kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.10kb.75mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.1kb.100mer *mappa.mm9.1kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.1kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.1kb.36mer` *mappa.mm9.1kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.1kb.40mer *mappa.mm9.1kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.1kb.40mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.1kb.50mer *mappa.mm9.1kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.1kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.1kb.75mer` *mappa.mm9.1kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.5kb.100mer *mappa.mm9.5kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.100mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.5kb.36mer *mappa.mm9.5kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.5kb.40mer` *mappa.mm9.5kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.5kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.5kb.50mer *mappa.mm9.5kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.50mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.5kb.75mer *mappa.mm9.5kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.75mer)
```


Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.exon.100mer` *mappa.mm9.exon.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.exon.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.exon.36mer *mappa.mm9.exon.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.exon.36mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.exon.40mer *mappa.mm9.exon.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.exon.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.exon.50mer` *mappa.mm9.exon.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.exon.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.exon.75mer *mappa.mm9.exon.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.exon.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.intron.100mer

mappa.mm9.intron.100mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.intron.36mer

mappa.mm9.intron.36mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.intron.40mer

mappa.mm9.intron.40mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.intron.50mer

mappa.mm9.intron.50mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.intron.75mer

mappa.mm9.intron.75mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_gene.100mer
mappa.mm9.nearest_gene.100mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.100mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_gene.36mer
mappa.mm9.nearest_gene.36mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.36mer)
```


Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_gene.40mer
mappa.mm9.nearest_gene.40mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

`data(mappa.mm9.nearest_gene.40mer)`

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_gene.50mer
mappa.mm9.nearest_gene.50mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.50mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_gene.75mer
mappa.mm9.nearest_gene.75mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_tss.100mer
mappa.mm9.nearest_tss.100mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_tss.36mer
mappa.mm9.nearest_tss.36mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.36mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_tss.40mer
mappa.mm9.nearest_tss.40mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_tss.50mer
mappa.mm9.nearest_tss.50mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.mm9.nearest_tss.75mer  
mappa.mm9.nearest_tss.75mer
```

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.nearest_tss.75mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs  
mappa  Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
peaks_E2F4
```

ChIP-seq Peaks for the E2F4 Transcription Factor

Description

A dataset containing the binding locations (peaks) of the transcription factor E2F4 called from a ChIP-seq experiment

Usage

```
peaks_E2F4
```

Format

A data frame containing 16,245 peak binding locations. Each row is a peak location, and the 3 variables/columns are chromosome, start peak coordinate, and end peak coordinate. Peak coordinates are in hg19 (UCSC) coordinates.

Source

The data and information regarding the experiment can be found in the following publication:

Lee, B. K., A. A. Bhingé, et al. (2011). "Wide-ranging functions of E2F4 in transcriptional activation and repression revealed by genome-wide analysis." *Nucleic Acids Res* 39(9): 3558-3573.

Examples

```
# Load E2F4 peak data.
data(peaks_E2F4)

# Print the first 10 peaks in the dataset.
print(head(peaks_E2F4))
```

peaks_H3K4me3_GM12878 *ChIP-seq Peaks for the Histone Modification H3K4me3 in GM12878*

Description

A dataset containing the binding locations (peaks) of the histone modification H3K4me3 called from a ChIP-seq experiment in the GM12878 cell line

Usage

```
peaks_H3K4me3_GM12878
```

Format

A data frame containing 57,476 peak binding locations. Each row is a peak location, and the 3 variables/columns are chromosome, start peak coordinate, and end peak coordinate. Peak coordinates are in hg19 (UCSC) coordinates.

Source

The data and information regarding the experiment can be found at the following ENCODE URL:

<http://hgdownload.cse.ucsc.edu/goldenPath/hg19/encodeDCC/wgEncodeBroadHistone/wgEncodeBroadHistoneGm12878>

Examples

```
# Load H3K4me3 in GM12878 peak data.
data(peaks_H3K4me3_GM12878)

# Print the first 10 peaks in the dataset.
print(head(peaks_H3K4me3_GM12878))
```

tss.danRer10	<i>tss.danRer10 TSS locations</i>
--------------	-----------------------------------

Description

A GRanges with all the TSSs for danRer10. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.danRer10
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.0 and org.Dr.eg.db_3.4.0.

tss.dm3	<i>tss.dm3 TSS locations</i>
---------	------------------------------

Description

A GRanges with all the TSSs for dm3. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.dm3
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.4.0.

tss.dm6

tss.dm6 TSS locations

Description

A GRanges with all the TSSs for dm6. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.dm6
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.3.0 and org.Dm.eg.db_3.4.0.

tss.hg19

tss.hg19 TSS locations

Description

A GRanges with all the TSSs for hg19. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.hg19
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.4.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.anno and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.Ent

tss.hg38

tss.hg38 TSS locations

Description

A GRanges with all the TSSs for hg38. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.hg38
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: `TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0` and `org.Hs.eg.db_3.4.0`. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

tss.mm10

tss.mm10 TSS locations

Description

A GRanges with all the TSSs for mm10. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.mm10
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: `TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0` and `org.Mm.eg.db_3.4.0`. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

`tss.mm9`*tss.mm9 TSS locations*

Description

A GRanges with all the TSSs for mm9. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage`tss.mm9`**Format**

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: `TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2` and `org.Mm.eg.db_3.4.0`. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

`tss.rn4`*tss.rn4 TSS locations*

Description

A GRanges with all the TSSs for rn4. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage`tss.rn4`**Format**

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2` and `org.Rn.eg.db_3.4.0`.

tss.rn5	<i>tss.rn5 TSS locations</i>
---------	------------------------------

Description

A GRanges with all the TSSs for rn5. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.rn5
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

tss.rn6	<i>tss.rn6 TSS locations</i>
---------	------------------------------

Description

A GRanges with all the TSSs for rn6. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.rn6
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.0 and org.Rn.eg.db_3.4.0.

Index

*Topic **classes**

GeneSet-class, [7](#)

LocusDefinition-class, [130](#)

*Topic **datasets**

geneset.biocarta_pathway.hsa, [8](#)

geneset.biocarta_pathway.mmu, [9](#)

geneset.biocarta_pathway.rno, [9](#)

geneset.ctd.hsa, [10](#)

geneset.cytoband.hsa, [10](#)

geneset.drug_bank.hsa, [11](#)

geneset.drug_bank.mmu, [11](#)

geneset.drug_bank.rno, [12](#)

geneset.ehmn_pathway_gene.hsa, [12](#)

geneset.ehmn_pathway_gene.mmu, [13](#)

geneset.ehmn_pathway_gene.rno, [13](#)

geneset.gene_expression.hsa, [14](#)

geneset.gene_expression.mmu, [14](#)

geneset.GOBP.dme, [15](#)

geneset.GOBP.dre, [15](#)

geneset.GOBP.hsa, [16](#)

geneset.GOBP.mmu, [17](#)

geneset.GOBP.rno, [17](#)

geneset.GOCC.dme, [18](#)

geneset.GOCC.dre, [19](#)

geneset.GOCC.hsa, [19](#)

geneset.GOCC.mmu, [20](#)

geneset.GOCC.rno, [21](#)

geneset.GOMF.dme, [21](#)

geneset.GOMF.dre, [22](#)

geneset.GOMF.hsa, [23](#)

geneset.GOMF.mmu, [23](#)

geneset.GOMF.rno, [24](#)

geneset.hallmark.hsa, [25](#)

geneset.immunologic.hsa, [25](#)

geneset.kegg_pathway.hsa, [26](#)

geneset.kegg_pathway.mmu, [27](#)

geneset.kegg_pathway.rno, [27](#)

geneset.mesh.hsa, [28](#)

geneset.mesh.mmu, [28](#)

geneset.mesh.rno, [29](#)

geneset.metabolite.hsa, [29](#)

geneset.metabolite.mmu, [30](#)

geneset.metabolite.rno, [30](#)

geneset.micrna.hsa, [31](#)

geneset.oncogenic.hsa, [31](#)

geneset.panther_pathway.hsa, [32](#)

geneset.panther_pathway.mmu, [33](#)

geneset.panther_pathway.rno, [33](#)

geneset.pfam.hsa, [34](#)

geneset.pfam.mmu, [34](#)

geneset.pfam.rno, [35](#)

geneset.protein_interaction_biogrid.hsa, [35](#)

geneset.reactome.dme, [36](#)

geneset.reactome.dre, [36](#)

geneset.reactome.hsa, [37](#)

geneset.reactome.mmu, [38](#)

geneset.reactome.rno, [38](#)

geneset.transcription_factors.hsa, [39](#)

geneset.transcription_factors.mmu, [40](#)

geneset.transcription_factors.rno, [40](#)

locusdef.danRer10.10kb, [41](#)

locusdef.danRer10.10kb_outside, [41](#)

locusdef.danRer10.10kb_outside_upstream, [42](#)

locusdef.danRer10.1kb, [43](#)

locusdef.danRer10.1kb_outside, [43](#)

locusdef.danRer10.1kb_outside_upstream, [44](#)

locusdef.danRer10.5kb, [45](#)

locusdef.danRer10.5kb_outside, [45](#)

locusdef.danRer10.5kb_outside_upstream, [46](#)

locusdef.danRer10.exon, [47](#)

locusdef.danRer10.intron, [47](#)

locusdef.danRer10.nearest_gene, [48](#)

locusdef.danRer10.nearest_tss, [49](#)

locusdef.dm3.10kb, [49](#)

locusdef.dm3.10kb_outside, [50](#)

locusdef.dm3.10kb_outside_upstream, [51](#)

locusdef.dm3.1kb, [52](#)

locusdef.dm3.1kb_outside, [52](#)

- locusdef.dm3.1kb_outside_upstream, [53](#)
- locusdef.dm3.5kb, [54](#)
- locusdef.dm3.5kb_outside, [54](#)
- locusdef.dm3.5kb_outside_upstream, [55](#)
- locusdef.dm3.exon, [56](#)
- locusdef.dm3.intron, [56](#)
- locusdef.dm3.nearest_gene, [57](#)
- locusdef.dm3.nearest_tss, [58](#)
- locusdef.dm6.10kb, [59](#)
- locusdef.dm6.10kb_outside, [59](#)
- locusdef.dm6.10kb_outside_upstream, [60](#)
- locusdef.dm6.1kb, [61](#)
- locusdef.dm6.1kb_outside, [61](#)
- locusdef.dm6.1kb_outside_upstream, [62](#)
- locusdef.dm6.5kb, [63](#)
- locusdef.dm6.5kb_outside, [63](#)
- locusdef.dm6.5kb_outside_upstream, [64](#)
- locusdef.dm6.exon, [65](#)
- locusdef.dm6.intron, [65](#)
- locusdef.dm6.nearest_gene, [66](#)
- locusdef.dm6.nearest_tss, [67](#)
- locusdef.hg19.10kb, [68](#)
- locusdef.hg19.10kb_outside, [68](#)
- locusdef.hg19.10kb_outside_upstream, [69](#)
- locusdef.hg19.1kb, [70](#)
- locusdef.hg19.1kb_outside, [71](#)
- locusdef.hg19.1kb_outside_upstream, [71](#)
- locusdef.hg19.5kb, [72](#)
- locusdef.hg19.5kb_outside, [73](#)
- locusdef.hg19.5kb_outside_upstream, [73](#)
- locusdef.hg19.exon, [74](#)
- locusdef.hg19.intron, [75](#)
- locusdef.hg19.nearest_gene, [75](#)
- locusdef.hg19.nearest_tss, [76](#)
- locusdef.hg38.10kb, [77](#)
- locusdef.hg38.10kb_outside, [78](#)
- locusdef.hg38.10kb_outside_upstream, [78](#)
- locusdef.hg38.1kb, [79](#)
- locusdef.hg38.1kb_outside, [80](#)
- locusdef.hg38.1kb_outside_upstream, [80](#)
- locusdef.hg38.5kb, [81](#)
- locusdef.hg38.5kb_outside, [82](#)
- locusdef.hg38.5kb_outside_upstream, [82](#)
- locusdef.hg38.exon, [83](#)
- locusdef.hg38.intron, [84](#)
- locusdef.hg38.nearest_gene, [84](#)
- locusdef.hg38.nearest_tss, [85](#)
- locusdef.mm10.10kb, [86](#)
- locusdef.mm10.10kb_outside, [87](#)
- locusdef.mm10.10kb_outside_upstream, [87](#)
- locusdef.mm10.1kb, [88](#)
- locusdef.mm10.1kb_outside, [89](#)
- locusdef.mm10.1kb_outside_upstream, [89](#)
- locusdef.mm10.5kb, [90](#)
- locusdef.mm10.5kb_outside, [91](#)
- locusdef.mm10.5kb_outside_upstream, [91](#)
- locusdef.mm10.exon, [92](#)
- locusdef.mm10.intron, [93](#)
- locusdef.mm10.nearest_gene, [93](#)
- locusdef.mm10.nearest_tss, [94](#)
- locusdef.mm9.10kb, [95](#)
- locusdef.mm9.10kb_outside, [96](#)
- locusdef.mm9.10kb_outside_upstream, [96](#)
- locusdef.mm9.1kb, [97](#)
- locusdef.mm9.1kb_outside, [98](#)
- locusdef.mm9.1kb_outside_upstream, [98](#)
- locusdef.mm9.5kb, [99](#)
- locusdef.mm9.5kb_outside, [100](#)
- locusdef.mm9.5kb_outside_upstream, [100](#)
- locusdef.mm9.exon, [101](#)
- locusdef.mm9.intron, [102](#)
- locusdef.mm9.nearest_gene, [102](#)
- locusdef.mm9.nearest_tss, [103](#)
- locusdef.rn4.10kb, [104](#)
- locusdef.rn4.10kb_outside, [105](#)
- locusdef.rn4.10kb_outside_upstream, [105](#)
- locusdef.rn4.1kb, [106](#)
- locusdef.rn4.1kb_outside, [107](#)
- locusdef.rn4.1kb_outside_upstream, [107](#)
- locusdef.rn4.5kb, [108](#)
- locusdef.rn4.5kb_outside, [109](#)
- locusdef.rn4.5kb_outside_upstream, [109](#)
- locusdef.rn4.exon, [110](#)
- locusdef.rn4.intron, [111](#)

- locusdef.rn4.nearest_gene, [111](#)
- locusdef.rn4.nearest_tss, [112](#)
- locusdef.rn5.10kb, [113](#)
- locusdef.rn5.10kb_outside, [113](#)
- locusdef.rn5.10kb_outside_upstream, [114](#)
- locusdef.rn5.1kb, [115](#)
- locusdef.rn5.1kb_outside, [115](#)
- locusdef.rn5.1kb_outside_upstream, [116](#)
- locusdef.rn5.5kb, [117](#)
- locusdef.rn5.5kb_outside, [117](#)
- locusdef.rn5.5kb_outside_upstream, [118](#)
- locusdef.rn5.exon, [119](#)
- locusdef.rn5.intron, [119](#)
- locusdef.rn5.nearest_gene, [120](#)
- locusdef.rn5.nearest_tss, [121](#)
- locusdef.rn6.10kb, [121](#)
- locusdef.rn6.10kb_outside, [122](#)
- locusdef.rn6.10kb_outside_upstream, [123](#)
- locusdef.rn6.1kb, [123](#)
- locusdef.rn6.1kb_outside, [124](#)
- locusdef.rn6.1kb_outside_upstream, [125](#)
- locusdef.rn6.5kb, [125](#)
- locusdef.rn6.5kb_outside, [126](#)
- locusdef.rn6.5kb_outside_upstream, [127](#)
- locusdef.rn6.exon, [127](#)
- locusdef.rn6.intron, [128](#)
- locusdef.rn6.nearest_gene, [129](#)
- locusdef.rn6.nearest_tss, [129](#)
- mappa.hg19.10kb.100mer, [131](#)
- mappa.hg19.10kb.24mer, [132](#)
- mappa.hg19.10kb.36mer, [132](#)
- mappa.hg19.10kb.40mer, [133](#)
- mappa.hg19.10kb.50mer, [134](#)
- mappa.hg19.10kb.75mer, [134](#)
- mappa.hg19.1kb.100mer, [135](#)
- mappa.hg19.1kb.24mer, [136](#)
- mappa.hg19.1kb.36mer, [136](#)
- mappa.hg19.1kb.40mer, [137](#)
- mappa.hg19.1kb.50mer, [138](#)
- mappa.hg19.1kb.75mer, [138](#)
- mappa.hg19.5kb.100mer, [139](#)
- mappa.hg19.5kb.24mer, [140](#)
- mappa.hg19.5kb.36mer, [140](#)
- mappa.hg19.5kb.40mer, [141](#)
- mappa.hg19.5kb.50mer, [142](#)
- mappa.hg19.5kb.75mer, [142](#)
- mappa.hg19.exon.100mer, [143](#)
- mappa.hg19.exon.24mer, [144](#)
- mappa.hg19.exon.36mer, [144](#)
- mappa.hg19.exon.40mer, [145](#)
- mappa.hg19.exon.50mer, [146](#)
- mappa.hg19.exon.75mer, [146](#)
- mappa.hg19.intron.100mer, [147](#)
- mappa.hg19.intron.24mer, [148](#)
- mappa.hg19.intron.36mer, [148](#)
- mappa.hg19.intron.40mer, [149](#)
- mappa.hg19.intron.50mer, [150](#)
- mappa.hg19.intron.75mer, [150](#)
- mappa.hg19.nearest_gene.100mer, [151](#)
- mappa.hg19.nearest_gene.24mer, [152](#)
- mappa.hg19.nearest_gene.36mer, [152](#)
- mappa.hg19.nearest_gene.40mer, [153](#)
- mappa.hg19.nearest_gene.50mer, [154](#)
- mappa.hg19.nearest_gene.75mer, [154](#)
- mappa.hg19.nearest_tss.100mer, [155](#)
- mappa.hg19.nearest_tss.24mer, [156](#)
- mappa.hg19.nearest_tss.36mer, [156](#)
- mappa.hg19.nearest_tss.40mer, [157](#)
- mappa.hg19.nearest_tss.50mer, [158](#)
- mappa.hg19.nearest_tss.75mer, [158](#)
- mappa.mm9.10kb.100mer, [159](#)
- mappa.mm9.10kb.36mer, [160](#)
- mappa.mm9.10kb.40mer, [160](#)
- mappa.mm9.10kb.50mer, [161](#)
- mappa.mm9.10kb.75mer, [162](#)
- mappa.mm9.1kb.100mer, [162](#)
- mappa.mm9.1kb.36mer, [163](#)
- mappa.mm9.1kb.40mer, [164](#)
- mappa.mm9.1kb.50mer, [164](#)
- mappa.mm9.1kb.75mer, [165](#)
- mappa.mm9.5kb.100mer, [166](#)
- mappa.mm9.5kb.36mer, [166](#)
- mappa.mm9.5kb.40mer, [167](#)
- mappa.mm9.5kb.50mer, [168](#)
- mappa.mm9.5kb.75mer, [168](#)
- mappa.mm9.exon.100mer, [169](#)
- mappa.mm9.exon.36mer, [170](#)
- mappa.mm9.exon.40mer, [170](#)
- mappa.mm9.exon.50mer, [171](#)
- mappa.mm9.exon.75mer, [172](#)
- mappa.mm9.intron.100mer, [172](#)
- mappa.mm9.intron.36mer, [173](#)
- mappa.mm9.intron.40mer, [174](#)
- mappa.mm9.intron.50mer, [174](#)
- mappa.mm9.intron.75mer, [175](#)
- mappa.mm9.nearest_gene.100mer, [176](#)
- mappa.mm9.nearest_gene.36mer, [176](#)

- mappa.mm9.nearest_gene.40mer, 177
- mappa.mm9.nearest_gene.50mer, 178
- mappa.mm9.nearest_gene.75mer, 178
- mappa.mm9.nearest_tss.100mer, 179
- mappa.mm9.nearest_tss.36mer, 180
- mappa.mm9.nearest_tss.40mer, 180
- mappa.mm9.nearest_tss.50mer, 181
- mappa.mm9.nearest_tss.75mer, 182
- peaks_E2F4, 182
- peaks_H3K4me3_GM12878, 183
- tss.danRer10, 184
- tss.dm3, 184
- tss.dm6, 185
- tss.hg19, 185
- tss.hg38, 186
- tss.mm10, 186
- tss.mm9, 187
- tss.rn4, 187
- tss.rn5, 188
- tss.rn6, 188

- chipenrich.data, 7, 9–14, 27–30, 32–35, 40, 131–182
- chipenrich.data-package
(chipenrich.data), 7

- GeneSet-class, 7
- geneset.biocarta_pathway.hsa, 8
- geneset.biocarta_pathway.mmu, 9
- geneset.biocarta_pathway.rno, 9
- geneset.ctd.hsa, 10
- geneset.cytoband.hsa, 10
- geneset.drug_bank.hsa, 11
- geneset.drug_bank.mmu, 11
- geneset.drug_bank.rno, 12
- geneset.ehmn_pathway_gene.hsa, 12
- geneset.ehmn_pathway_gene.mmu, 13
- geneset.ehmn_pathway_gene.rno, 13
- geneset.gene_expression.hsa, 14
- geneset.gene_expression.mmu, 14
- geneset.GOBP.dme, 15
- geneset.GOBP.dre, 15
- geneset.GOBP.hsa, 16
- geneset.GOBP.mmu, 17
- geneset.GOBP.rno, 17
- geneset.GOCC.dme, 18
- geneset.GOCC.dre, 19
- geneset.GOCC.hsa, 19
- geneset.GOCC.mmu, 20
- geneset.GOCC.rno, 21
- geneset.GOMF.dme, 21
- geneset.GOMF.dre, 22
- geneset.GOMF.hsa, 23
- geneset.GOMF.mmu, 23
- geneset.GOMF.rno, 24
- geneset.hallmark.hsa, 25
- geneset.immunologic.hsa, 25
- geneset.kegg_pathway.hsa, 26
- geneset.kegg_pathway.mmu, 27
- geneset.kegg_pathway.rno, 27
- geneset.mesh.hsa, 28
- geneset.mesh.mmu, 28
- geneset.mesh.rno, 29
- geneset.metabolite.hsa, 29
- geneset.metabolite.mmu, 30
- geneset.metabolite.rno, 30
- geneset.microna.hsa, 31
- geneset.oncogenic.hsa, 31
- geneset.panther_pathway.hsa, 32
- geneset.panther_pathway.mmu, 33
- geneset.panther_pathway.rno, 33
- geneset.pfam.hsa, 34
- geneset.pfam.mmu, 34
- geneset.pfam.rno, 35
- geneset.protein_interaction_biogrid.hsa, 35
- geneset.reactome.dme, 36
- geneset.reactome.dre, 36
- geneset.reactome.hsa, 37
- geneset.reactome.mmu, 38
- geneset.reactome.rno, 38
- geneset.transcription_factors.hsa, 39
- geneset.transcription_factors.mmu, 40
- geneset.transcription_factors.rno, 40

- locusdef.danRer10.10kb, 41
- locusdef.danRer10.10kb_outside, 41
- locusdef.danRer10.10kb_outside_upstream, 42
- locusdef.danRer10.1kb, 43
- locusdef.danRer10.1kb_outside, 43
- locusdef.danRer10.1kb_outside_upstream, 44
- locusdef.danRer10.5kb, 45
- locusdef.danRer10.5kb_outside, 45
- locusdef.danRer10.5kb_outside_upstream, 46
- locusdef.danRer10.exon, 47
- locusdef.danRer10.intron, 47
- locusdef.danRer10.nearest_gene, 48
- locusdef.danRer10.nearest_tss, 49
- locusdef.dm3.10kb, 49
- locusdef.dm3.10kb_outside, 50
- locusdef.dm3.10kb_outside_upstream, 51
- locusdef.dm3.1kb, 52
- locusdef.dm3.1kb_outside, 52

- locusdef.dm3.1kb_outside_upstream, 53
- locusdef.dm3.5kb, 54
- locusdef.dm3.5kb_outside, 54
- locusdef.dm3.5kb_outside_upstream, 55
- locusdef.dm3.exon, 56
- locusdef.dm3.intron, 56
- locusdef.dm3.nearest_gene, 57
- locusdef.dm3.nearest_tss, 58
- locusdef.dm6.10kb, 59
- locusdef.dm6.10kb_outside, 59
- locusdef.dm6.10kb_outside_upstream, 60
- locusdef.dm6.1kb, 61
- locusdef.dm6.1kb_outside, 61
- locusdef.dm6.1kb_outside_upstream, 62
- locusdef.dm6.5kb, 63
- locusdef.dm6.5kb_outside, 63
- locusdef.dm6.5kb_outside_upstream, 64
- locusdef.dm6.exon, 65
- locusdef.dm6.intron, 65
- locusdef.dm6.nearest_gene, 66
- locusdef.dm6.nearest_tss, 67
- locusdef.hg19.10kb, 68
- locusdef.hg19.10kb_outside, 68
- locusdef.hg19.10kb_outside_upstream, 69
- locusdef.hg19.1kb, 70
- locusdef.hg19.1kb_outside, 71
- locusdef.hg19.1kb_outside_upstream, 71
- locusdef.hg19.5kb, 72
- locusdef.hg19.5kb_outside, 73
- locusdef.hg19.5kb_outside_upstream, 73
- locusdef.hg19.exon, 74
- locusdef.hg19.intron, 75
- locusdef.hg19.nearest_gene, 75
- locusdef.hg19.nearest_tss, 76
- locusdef.hg38.10kb, 77
- locusdef.hg38.10kb_outside, 78
- locusdef.hg38.10kb_outside_upstream, 78
- locusdef.hg38.1kb, 79
- locusdef.hg38.1kb_outside, 80
- locusdef.hg38.1kb_outside_upstream, 80
- locusdef.hg38.5kb, 81
- locusdef.hg38.5kb_outside, 82
- locusdef.hg38.5kb_outside_upstream, 82
- locusdef.hg38.exon, 83
- locusdef.hg38.intron, 84
- locusdef.hg38.nearest_gene, 84
- locusdef.hg38.nearest_tss, 85
- locusdef.mm10.10kb, 86
- locusdef.mm10.10kb_outside, 87
- locusdef.mm10.10kb_outside_upstream, 87
- locusdef.mm10.1kb, 88
- locusdef.mm10.1kb_outside, 89
- locusdef.mm10.1kb_outside_upstream, 89
- locusdef.mm10.5kb, 90
- locusdef.mm10.5kb_outside, 91
- locusdef.mm10.5kb_outside_upstream, 91
- locusdef.mm10.exon, 92
- locusdef.mm10.intron, 93
- locusdef.mm10.nearest_gene, 93
- locusdef.mm10.nearest_tss, 94
- locusdef.mm9.10kb, 95
- locusdef.mm9.10kb_outside, 96
- locusdef.mm9.10kb_outside_upstream, 96
- locusdef.mm9.1kb, 97
- locusdef.mm9.1kb_outside, 98
- locusdef.mm9.1kb_outside_upstream, 98
- locusdef.mm9.5kb, 99
- locusdef.mm9.5kb_outside, 100
- locusdef.mm9.5kb_outside_upstream, 100
- locusdef.mm9.exon, 101
- locusdef.mm9.intron, 102
- locusdef.mm9.nearest_gene, 102
- locusdef.mm9.nearest_tss, 103
- locusdef.rn4.10kb, 104
- locusdef.rn4.10kb_outside, 105
- locusdef.rn4.10kb_outside_upstream, 105
- locusdef.rn4.1kb, 106
- locusdef.rn4.1kb_outside, 107
- locusdef.rn4.1kb_outside_upstream, 107
- locusdef.rn4.5kb, 108
- locusdef.rn4.5kb_outside, 109
- locusdef.rn4.5kb_outside_upstream, 109
- locusdef.rn4.exon, 110
- locusdef.rn4.intron, 111
- locusdef.rn4.nearest_gene, 111
- locusdef.rn4.nearest_tss, 112
- locusdef.rn5.10kb, 113
- locusdef.rn5.10kb_outside, 113
- locusdef.rn5.10kb_outside_upstream, 114
- locusdef.rn5.1kb, 115
- locusdef.rn5.1kb_outside, 115
- locusdef.rn5.1kb_outside_upstream, 116
- locusdef.rn5.5kb, 117
- locusdef.rn5.5kb_outside, 117
- locusdef.rn5.5kb_outside_upstream, 118
- locusdef.rn5.exon, 119
- locusdef.rn5.intron, 119
- locusdef.rn5.nearest_gene, 120
- locusdef.rn5.nearest_tss, 121

- locusdef.rn6.10kb, [121](#)
- locusdef.rn6.10kb_outside, [122](#)
- locusdef.rn6.10kb_outside_upstream, [123](#)
- locusdef.rn6.1kb, [123](#)
- locusdef.rn6.1kb_outside, [124](#)
- locusdef.rn6.1kb_outside_upstream, [125](#)
- locusdef.rn6.5kb, [125](#)
- locusdef.rn6.5kb_outside, [126](#)
- locusdef.rn6.5kb_outside_upstream, [127](#)
- locusdef.rn6.exon, [127](#)
- locusdef.rn6.intron, [128](#)
- locusdef.rn6.nearest_gene, [129](#)
- locusdef.rn6.nearest_tss, [129](#)
- LocusDefinition-class, [130](#)
- mappa.hg19.10kb.100mer, [131](#)
- mappa.hg19.10kb.24mer, [132](#)
- mappa.hg19.10kb.36mer, [132](#)
- mappa.hg19.10kb.40mer, [133](#)
- mappa.hg19.10kb.50mer, [134](#)
- mappa.hg19.10kb.75mer, [134](#)
- mappa.hg19.1kb.100mer, [135](#)
- mappa.hg19.1kb.24mer, [136](#)
- mappa.hg19.1kb.36mer, [136](#)
- mappa.hg19.1kb.40mer, [137](#)
- mappa.hg19.1kb.50mer, [138](#)
- mappa.hg19.1kb.75mer, [138](#)
- mappa.hg19.5kb.100mer, [139](#)
- mappa.hg19.5kb.24mer, [140](#)
- mappa.hg19.5kb.36mer, [140](#)
- mappa.hg19.5kb.40mer, [141](#)
- mappa.hg19.5kb.50mer, [142](#)
- mappa.hg19.5kb.75mer, [142](#)
- mappa.hg19.exon.100mer, [143](#)
- mappa.hg19.exon.24mer, [144](#)
- mappa.hg19.exon.36mer, [144](#)
- mappa.hg19.exon.40mer, [145](#)
- mappa.hg19.exon.50mer, [146](#)
- mappa.hg19.exon.75mer, [146](#)
- mappa.hg19.intron.100mer, [147](#)
- mappa.hg19.intron.24mer, [148](#)
- mappa.hg19.intron.36mer, [148](#)
- mappa.hg19.intron.40mer, [149](#)
- mappa.hg19.intron.50mer, [150](#)
- mappa.hg19.intron.75mer, [150](#)
- mappa.hg19.nearest_gene.100mer, [151](#)
- mappa.hg19.nearest_gene.24mer, [152](#)
- mappa.hg19.nearest_gene.36mer, [152](#)
- mappa.hg19.nearest_gene.40mer, [153](#)
- mappa.hg19.nearest_gene.50mer, [154](#)
- mappa.hg19.nearest_gene.75mer, [154](#)
- mappa.hg19.nearest_tss.100mer, [155](#)
- mappa.hg19.nearest_tss.24mer, [156](#)
- mappa.hg19.nearest_tss.36mer, [156](#)
- mappa.hg19.nearest_tss.40mer, [157](#)
- mappa.hg19.nearest_tss.50mer, [158](#)
- mappa.hg19.nearest_tss.75mer, [158](#)
- mappa.mm9.10kb.100mer, [159](#)
- mappa.mm9.10kb.36mer, [160](#)
- mappa.mm9.10kb.40mer, [160](#)
- mappa.mm9.10kb.50mer, [161](#)
- mappa.mm9.10kb.75mer, [162](#)
- mappa.mm9.1kb.100mer, [162](#)
- mappa.mm9.1kb.36mer, [163](#)
- mappa.mm9.1kb.40mer, [164](#)
- mappa.mm9.1kb.50mer, [164](#)
- mappa.mm9.1kb.75mer, [165](#)
- mappa.mm9.5kb.100mer, [166](#)
- mappa.mm9.5kb.36mer, [166](#)
- mappa.mm9.5kb.40mer, [167](#)
- mappa.mm9.5kb.50mer, [168](#)
- mappa.mm9.5kb.75mer, [168](#)
- mappa.mm9.exon.100mer, [169](#)
- mappa.mm9.exon.36mer, [170](#)
- mappa.mm9.exon.40mer, [170](#)
- mappa.mm9.exon.50mer, [171](#)
- mappa.mm9.exon.75mer, [172](#)
- mappa.mm9.intron.100mer, [172](#)
- mappa.mm9.intron.36mer, [173](#)
- mappa.mm9.intron.40mer, [174](#)
- mappa.mm9.intron.50mer, [174](#)
- mappa.mm9.intron.75mer, [175](#)
- mappa.mm9.nearest_gene.100mer, [176](#)
- mappa.mm9.nearest_gene.36mer, [176](#)
- mappa.mm9.nearest_gene.40mer, [177](#)
- mappa.mm9.nearest_gene.50mer, [178](#)
- mappa.mm9.nearest_gene.75mer, [178](#)
- mappa.mm9.nearest_tss.100mer, [179](#)
- mappa.mm9.nearest_tss.36mer, [180](#)
- mappa.mm9.nearest_tss.40mer, [180](#)
- mappa.mm9.nearest_tss.50mer, [181](#)
- mappa.mm9.nearest_tss.75mer, [182](#)
- peaks_E2F4, [182](#)
- peaks_H3K4me3_GM12878, [183](#)
- tss.danRer10, [184](#)
- tss.dm3, [184](#)
- tss.dm6, [185](#)
- tss.hg19, [185](#)
- tss.hg38, [186](#)
- tss.mm10, [186](#)
- tss.mm9, [187](#)
- tss.rn4, [187](#)
- tss.rn5, [188](#)

tss.rn6, [188](#)